

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: SALINE	NE $\frac{1}{4}$ NE $\frac{1}{4}$ SW $\frac{1}{4}$	25	T 14 S	R 3 E/W

Distance and direction from nearest town or city street address of well if located within city?

420 E. WAYNE

2 WATER WELL OWNER: DON VANDEGRIFT	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 420 E. WAYNE	Application Number:
City, State, ZIP Code: SALINA, KS. 67401	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 54.2 ft. ELEVATION: 1240
	Depth(s) Groundwater Encountered 1. 11.5 ft. 2. 11.5 ft. 3. 11.5 ft.
	WELL'S STATIC WATER LEVEL 11.5 ft. below land surface measured on mo/day/yr 6-5-95
	Pump test data: Well water was 12.10 ft. after 1 hours pumping 30 gpm
	Est. Yield 100 gpm: Well water was 12.10 ft. after 1 hours pumping 30 gpm
	Bore Hole Diameter 9 in. to 56 ft., and 56 in. to 56 ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 <u>Lawn and garden only</u> 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes X No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 44 ft., Dia 16 in. to 160 ft., Dia 160 in. to 160 ft., Dia 160 in. to 160 ft.			Threaded
Casing height above land surface 16 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 26			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot .035	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS: From 44 ft. to 54 ft., From 54 ft. to 54 ft., From 54 ft. to 54 ft., From 54 ft. to 54 ft.			
GRAVEL PACK INTERVALS: From 22 ft. to 54 ft., From 54 ft. to 54 ft., From 54 ft. to 54 ft., From 54 ft. to 54 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 <u>Bentonite</u>	4 Other
GROUT INTERVALS: From 0 ft. to 22 ft., From 22 ft. to 22 ft., From 22 ft. to 22 ft., From 22 ft. to 22 ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 <u>Watertight sewer lines</u>	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? EAST				
How many feet? 20				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	FILL DIRT			
2	18	CLAY TAN SILTY			
18	47	SAND FINE TAN			
47	46.5	CLAY GRAY SOFT			
46.5	54.2	SAND FINE TO COARSE TAN			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-5-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 388 This Water Well Record was completed on (mo/day/yr) 6-5-95 under the business name of PESTINGER PUMP SERVICE by (signature) <i>Paul Kucyko</i>
