

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SALINE		SW 1/4 NE 1/4 SE 1/4	25	T 14 S	R 3 E
Distance and direction from nearest town or city street address of well if located within city?					
2289 ROACH					
2 WATER WELL OWNER: XRAYMOND X MIKE DOLTON		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # 2289 ROACH		Application Number:			
City, State, ZIP Code SALINA, KS. 67401					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 47.8 ft. ELEVATION: 1240			
		Depth(s) Groundwater Encountered 1. 11.8 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 11.8 ft. below land surface measured on mo/day/yr 4-16-96			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 75+ gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 in. to 48 ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped			
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded					
2 PVC 4 ABS 7 Fiberglass Threaded					
Blank casing diameter 5 in. to 38 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface 18 in. weight 160 lbs./ft. Wall thickness or gauge No. SDR 26					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot .035 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 38 ft. to 47.8 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 30 ft. to 47.8 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout intervals: From 5 ft. to 28 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? EAST		How many feet? 11			
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0 4 FILL DIRT					
4 10 CLAY GRAY SOFT					
10 19 SANDY LOOM TAN					
19 37 SAND TAN FINE					
37 38 CLAY GRAY SOFT					
38 47.8 SANS FINE TO MED. TAN					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-16-96 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 388 This Water Well Record was completed on (mo/day/yr) 4-16-96					
under the business name of PESTINGER PUMP SERVICE by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					