5NMW-53 2311138 v	VATER WELL RECORD Fo	rm WWC-5	KSA 82a-1	212		
LOCATION OF WATER WELL: Fraction	n ,	Section	Number	Township Number	Range Number	
County: Saline No		1/4		T /4 S	LR 3 EW	
Distance and direction from nearest town or city str	eet address of well if located v	vithin city?				
1000 COLLOCA III	31 (1) F)(XI)	wp_				
WATER WELL OWNER: $$	DHE	ı				
RR#, St. Address, Box # :	Forbus Field, Bld	9740		Board of Agriculture	, Division of Water Resources	
City, State, ZIP Code :	Topeka KS Col	2620-00	001	Application Number		
LOCATE WELL'S LOCATION WITH 4 DEPTH	OF COMPLETED WELL			ON:		
AN "X" IN SECTION BOX: Depth(s) G	roundwater Encountered 1	· 	ft. 2.	, , ft.	3	
WELL'S ST	TATIC WATER LEVEL . 25.	7.6. ft. below	land surfa	ce measured on mo/day/	yr . 5.5.5.9.6	
	Pump test data: Well water v	vas	ft. afte	er hours	pumping gpm	
Est. Yield	gpm: Well water v					
'	Diameter 8 . 2 . 5 in . to					
A/ Supramonantenessessessessessessessessessessessesses		Public water sur			1 Injection well	
1 Dom				Dewatering 1	2 Other (Specify below)	
2 Irriga	ation 4 Industrial 7	Lawn and garde	n only 10	Monitoring well		
	nical/bacteriological sample sub					
S mitted		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		r Well Disinfected? Yes	No X	
TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete ti			ued Clamped	
1 Steel 3 RMP (SR)	6 Asbestos-Cement	9 Other (spec			elded	
2 PVC 4 ABS	7 Fiberglass		• •	· · · · · · · · · · · · · · · · · · ·	readed) Flush	
Blank casing diameter in. to				The state of the s	AND	
Casing height above land surface.	in weight 4 7.C	3	lhe /ft	Wall thickness or gauge	No 500 40	
TYPE OF SCREEN OR PERFORATION MATERIA		7 PVC		10 Asbestos-ce		
1 Steel 3 Stainless steel	5 Fiberglass	8 RMP (S			fy)	
	6 Concrete tile	9 ABS	,, ,,	12 None used	•	
2 Brass 4 Galvanized steel SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed			8 Saw cut	11 None (open hole)	
and the second s	S Gauzeu  S Gauzeu  S Wire wr			9 Drilled holes	11 None (open hole)	
Control of the Contro	7 Torch ci	• •			,	
2 Louvered shutter 4 Key punched		- ""			t. toft.	
SCREEN-PERFORATED INTERVALS: From.	ft. to					
GRAVEL PACK INTERVALS: From	2 5 to to	50	ft From	4	i. toft.	
From	ft. to	a a Secondaria di aliana di al	ft., From		t. to ft.	
6 GROUT MATERIAL: 1 Neat cement	2 Coment grout	Bentonite	NAME .		,	
Grout Intervals: From O	2 Cement grout 29 ft., From	& DEDITIONS				
What is the nearest source of possible contaminati	i i				Abandoned water well	
•	·					
	•		11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below)			
	2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard		13 Insecticide storage			
3 Watertight sewer lines 6 Seepage pit	9 Feedyard		How many	•		
Direction from well? FROM TO LITHOL	OGIC LOG	FROM	TO TIALLY		3 INTERVALS	
5 13 Silt, Son	re Clay					
13 38 Self win	A STATE OF THE PARTY OF THE PAR	yer				
3 30 300	i de	TVI -		A LANGUAGE STREET, THE STREET,		
38 40 Clay 05	e Silt			LANGER CONTROL OF THE	Monorani	
38 40 Clay son						
	4					
45 50 Sand, Sel	4					
			***************************************			
				AND AND A TOTAL OF THE PARTY OF		
					NT-27	
AND THE RESERVE OF THE PROPERTY OF THE PROPERT						
					4 di	
7 CONTRACTOR'S OR LANDOWNER'S CERTIF						
	FICATION: This water well was	() constructed	l, (2) recor	structed, or (3) plugged	under my jurisdiction and was	
completed on (mo/day/year)	# 5.5.7.6	and	this record	d is true to the best of my	knowledge, and belief. Kansas	
completed on (mo/day/year)	FICATION: This water well was	and	this record	d is true to the best of my	under my jurisdiction and was knowledge and belief. Kansas	
completed on (mo/day/year)	5-5-7.6 7	Il Record was co	this record completed on by (signati	d is true to the best of my n (mo/day/yr) 5 ure)	knowledge and belief. Kansas 70-96 Yur	