SNMW-8D 2311138	WATER WELL RECORD Form W	WC-5 KSA 82a	-1212		
1 LOCATION OF WATER WELL: Fracti		Section Number		per Range	Number
County: Saline Su	0 14 NW 14 SW 14	12	T 14	SR	$\Sigma \in \mathcal{N}(V)$
Distance and direction from nearest town or city s	treet address of well if located within	city?	1		
West of 7th st. mich	I way between	Pine	delm	Streets	
2 WATER WELL OWNER: KOT	·		b		
	bus Field, Bldg 740		Board of Agric	culture, Division of Wa	ater Resources
City, State, ZIP Code : Tou	Deta KS 66620-6	2001	Application Nu	ımber:	
	OF COMPLETED WELL				
LANDOW IN OFFICIAL DOV.	Groundwater Encountered 1				· ·
WELL'S S	Pump test data: Well water was gpm: Well water was blameter.	tt. below land succession ft. a	face measured on months fiter	o/day/yr . 4-25- ours pumping ours pumping in. to	gpm gt.
X_sw SE 1 Dor		eld water supply	9 Dewatering	12 Other (Specif	y below)
2 Irrig	gation 4 Industrial 7 Lawn	and garden only	10 Monitoring well	. .,	
Was a che	emical/bacteriological sample submitted	d to Department? Y	esNoX	.; If yes, mo/day/yr sa	ample was sub-
S mitted		Wa	ter Well Disinfected?	Yes No-	
5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 (Concrete tile	CASING JOINTS	S: Glued Cla	mped
1 Steel 3 RMP (SR)	6 Asbestos-Cement 9 (Other (specify below	w)	Welded	
2 PVC 4 ABS	7 Fiberglass			Threaded. F.I.W.	5/-
Blank casing diameter Z in. to , .		in. to	ft., Dia	in. to , .	ft.
Casing height above land surface. Fush	in., weight				40
TYPE OF SCREEN OR PERFORATION MATERIA	, ,	7 PVC	10 Asbest	•	
	· - ·	8 RMP (SR)		specify)	
	5 Fiberglass 6 Concrete tile	9 ABS		ised (open hole)	
2 Brass 4 Galvanized steel				` '	non bolo)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapp	•	8 Saw cut	11 None (o	pen noie)
1 Continuous slot 3 Mill slot	6 Wire wrapped		9 Drilled holes		
2 Louvered shutter 4 Key punched		2	10 Other (specify) .		Į.
SCREEN-PERFORATED INTERVALS: From.	ft. to 6.	, -	m <i>.</i>		
From.	16 ft. to	ft., Fro. ـ ـ ـ ـ ـ	m	ft. to	
GRAVEL PACK INTERVALS: From.	\mathcal{L} \mathcal{L} \mathcal{L} \mathcal{L} .	,	m		
From	ft. to	ft., Fro	· · · · · · · · · · · · · · · · · · ·	ft. to	π.
6 GROUT MATERIAL: 1 Neat cement	CLG		Other		
Grout Intervals: From U . S ft. to	T. J ft., From	. ft. to	ft., From	ft. to	
What is the nearest source of possible contamina	tion:	10 Lives	stock pens	14 Abandoned wa	iter well
1 Septic tank 4 Lateral lines	7 Pit privy	11 Fuel	storage	15 Oil well/Gas w	ell
2 Sewer lines 5 Cess pool	8 Sewage lagoon	12 Ferti	izer storage	16 Other (specify	below)
3 Watertight sewer lines 6 Seepage pit	9 Feedyard	13 Insec	cticide storage		
Direction from well?		How ma	ny feet?		
FROM TO LITHOL	OGIC LOG FRO	ОМ ТО	PLUG	GING INTERVALS	
30 38 Clay, Sil	thy			The second section of the se	
30 38 Clay Sul					
44.4 50.4 Sund					
50.4 50.8 Clay, Selt	11 Sandy				
50.8 59.71 Sand	7, 3				
597 60.3 Clay, Sit	*				
60.3 LO.5 Sund					**************************************
60.5 60.8 Clay Su	1.				
10.8 63 Sand					
(3 65 Selt, Cla					
65 65 Sec, Cla	yu -				
	<u> </u>				
7 CONTRACTOR'S OR LANDOWNER'S CERTI	FICATION: This water well was 111 c	onstructed, (2) rec	onstructed, or (3) plua	ged under my jurisdi	ction and was
completed on (mo/day/year) 4-25-9	L		ord is true to the best of		
president and the state of the	5/ This Water Well Reco			5-21-961	
under the business name of	2	by (signa		0/	4 - /
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE	PRESS FIRMLY and PRINT clearly Please fill in			top three copies to Kansar	s Department
	ras 66620,0001 Telephone: 913-296-5545 Send				-1