

1 LOCATION OF WATER WELL: SALINE		Fraction NE 1/4 SW 1/4 NW 1/4		Section Number 36	Township Number T 14 S	Range Number R 3 EW
Distance and direction from nearest town or city street address of well if located within city? 2506 ROCKHURST RD.						
2 WATER WELL OWNER: MIKE WALLACE RR#, St. Address, Box #: 2506 ROCKHURST RD. City, State, ZIP Code: SALINA, KS. 67401 Board of Agriculture, Division of Water Resources Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 59 ft. ELEVATION: 1241				
		Depth(s) Groundwater Encountered 1. 16.5 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 16.5 ft. below land surface measured on mo/day/yr 6-10-96 Pump test data: Well water was 24.7 ft. after 1 hours pumping 20 gpm Est. Yield 75 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 60 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No				
5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 5 in. to 49 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 16 in. weight 160 lbs./ft. Wall thickness or gauge No. SDR 26 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot .035 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 49 ft. to 59 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 40 ft. to 59 ft. From ft. to ft. From ft. to ft. From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 23 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? SOUTH How many feet? 18						
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS				
0	3	FILL DIRT				
3	27	CLAY TAN SILTY				
27	49	SAND FINE TAN				
49	50	CLAY GRAY				
50	59	SAND FINE TAN				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-10-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 388 This Water Well Record was completed on (mo/day/yr) 6-10-96 under the business name of PESTINGER PUMP SERVICE by (signature) [Signature]						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						