<u> </u>			WATE	er well record	D Form W		KSA 82a-				
1 LOCATIO	N OF WAT	ER WELL:	Fraction			Section	on Number	Township N		Range Number	
County:	SALINE		NW V		SE 1/4		26	T 14	S	<u> </u>	
Distance an	d direction	rrom nearest tov	-	address of well if lo	ocated within o	ity?				Allenen	
1		digita pilan manin de me en		RGURY AV.							
			RHODENBAUG	ri							
		#:449 ME						Board of A	griculture,	Division of Water Resources	
City, State, ZIP Code : SALINA, KS. 67401						Application Number:					
LOCATE AN "X" II	WELL'S LON	CATION WITH I BOX:	4 DEPTH OF	COMPLETED WEL	L52.•4	, 10 1	ft. ELEVAT	TON: 1240			
Ť		t k	WELL'S STATION	WATER LEVEL	17 . 11	ft. bel	low land surf	ace measured or	mo/day/yr	3	
	- NW	NE	Est. Yield . 60	gpm: Well	water was	er was 23 ft. after 1 hours pumping 30 gpm er was ft. after hours pumping gpm					
* w -		municipality E	l			54ft., and					
≥		X		TO BE USED AS:			,	3 Air conditioning		Injection well	
	_ SW	SE	1 Domestic		6 Oil fiel	d wate	r supply	9 Dewatering	12	Other (Specify below)	
	1	8	2 Irrigation								
<u> </u>	<u> </u>		Was a chemical mitted	/bacteriological san	nple submitted	to Dep		er Well Disinfecte	d? Yes	s, mo/day/yr sample was sub X No	
5 TYPE O	F BLANK C	ASING USED:		5 Wrought iron	8 C	oncret	e tile	CASING JO	INTS: Glue	ed 🗓 Clamped	
ب 1 Stee	el	3 RMP (S	R)	6 Asbestos-Cen		ther (s	specify below			ded	
2 PV		4 ABS		7 Fiberglass						eaded	
										in. to ft.	
Casing heig	jht above la	nd surface	. 14	in., weight	160		lbs./f	t. Wall thickness	or gauge N	vo. SDR 26	
TYPE OF SCREEN OR PERFORATION MATERIAL:					our have not been produced and the second			10 Asbestos-cement			
1 Steel 3 Stainless steel				5 Fiberglass 8 RMF			(SR)	11 Oth	er (specify	·)	
2 Brass 4 Galvanized steel				6 Concrete tile	tile 9 ABS			12 No	ne used (o	pen hole)	
SCREEN OR PERFORATION OPENINGS ARE:					Gauzed wrapp	ed		8 Saw cut		11 None (open hole)	
1 Con	ntinuous slo	t 3N	Mill slot .035	6 \	Wire wrapped			9 Drilled holes			
	vered shutte		(ey punched	7	Torch cut	Ja		10 Other (specif	y)		
SCREEN-P	ERFORATE	D INTERVALS:								toft.	
										toft.	
G	RAVEL PAG	CK INTERVALS:	From		to 52 to	·4	ft., Fron ft., Fron			to	
6 GROUT			cement	2 Cement grout	3_1		ite 4 (Other			
Grout Interv			.ft. to 23.							ft. to	
What is the		urce of possible					10 Livest			Abandoned water well	
1 Septic tank 4 Lateral lines				7 Pit priv	'y		11 Fuel s			Oil well/Gas well	
2 Sewer lines 5 Cess pool			•	, ,			zer storage	16 (Other (specify below)		
3 Watertight sewer lines 6 Seepage pit				9 Feedya		13 Insecticide storage					
Direction from	om well?	NORT	'HEAST'				How mar	y feet? 2	5		
FROM	TO	deal wheels als gloring	LITHOLOGIC	LOG	FRC	M	то	P	LUGGING	INTERVALS	
3	3 36		M SILTY								
36	53		NE TO COAR	SE			(1976-1974) (1974-1974) (1984-1984) (1984-1974) (1984-1974) (1984-1974) (1984-1974)				
53	54	SHALE I	J. GREEN						***************************************	W	
				VA./ 1. (1. (1. (1. (1. (1. (1. (1. (1. (1.						CARROLLE GENERAL CONTRACTOR AND CONT	
								-	,		
								and the second s			
7 CONTR	ACTOR'S	OR LANDOWNE	R'S CERTIFICA	TION: This water v	vell was (1).cc	nstruc	ted, (2) reco	nstructed, or (3)	plugged ur	nder my jurisdiction and was	
completed			22-96							nowledge and belief. Kansas	
Water Well	Contractor'	s License No	388	This Wa	ater Well Reco	rd was	completed	n (mo/day/yr) .	M. 1. 8	3 -J 22 -j 96	
under the b	ousiness na	me of PESTIN	NGER PUMP S	SERVICE			by (signat	1 miles	A JA	ely &	
									1	7	