

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Saline		NE 1/4 SE 1/4 SE 1/4	27	T 14 S	R 3
Distance and direction from nearest town or city street address of well if located within city? Well # 99M20 at former Schilling AFB, Salina KS					
2 WATER WELL OWNER: USACE % Burns & McDonnell		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: 9400 Ward Pkwy		Application Number:			
City, State, ZIP Code: Kansas City MO 64114					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;">N W      E SW      SE X S</div>		4 DEPTH OF COMPLETED WELL: 23.5 ft. ELEVATION: Depth(s) Groundwater Encountered 1. .ft. 2. .ft. 3. .ft. WELL'S STATIC WATER LEVEL: 5.9 ft. below land surface measured on mo/day/yr 1/6/97 Pump test data: Well water was .ft. after . hours pumping gpm Est. Yield gpm: Well water was .ft. after . hours pumping gpm Bore Hole Diameter: 8 in. to 24 .ft., and .in. to .ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter: 2 in. to 13.1 ft., Dia .in. to .ft., Dia .in. to .ft. Casing height above land surface: 0 * .in., weight .lbs./ft. Wall thickness or gauge No. Sch 40		CASING JOINTS: Glued Clamped Welded Threaded X 6 Concrete tile 7 Fiberglass 8 RMP (SR) 9 Other (specify below) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 3 Gauzed wrapped 4 Wire wrapped 5 Drilled holes 6 Torch cut 7 Other (specify) 2 Louvered shutter 3 Key punched 4 Concrete tile 5 ABS 6 None used (open hole)			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)		SCREEN-PERFORATED INTERVALS: From 13.1 ft. to 23.1 ft., From .ft. to .ft. GRAVEL PACK INTERVALS: From 10 ft. to 24 ft., From .ft. to .ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 10 ft. to 7 ft., From 7 ft. to 3 ft., From .ft. to .ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Former AFB Direction from well? How many feet?		PLUGGING INTERVALS			
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0 24 Silty clays, sandy clays					
* Flush mount well cover variance granted by KDHE letter dated 10/2/96					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/5/96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 570 This Water Well Record was completed on (mo/day/yr) 1/23/97 under the business name of AQUADRILL, INC. by signature Jeff Jahn					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					