• 1 • 1	WATER	WELL RECORD FO	orm WWC-5	KSA 82a	.1212			
LOCATION OF WATER WELL:	Fraction	111.150	Sec	tion Number	T	p Number	1	Number
County: Oistance and direction from nearest town	or city street add	Iress of well if located	1/4 within city?	<u> </u>	<u> </u>	14 6)	<u> R</u>	Z BOW
	or only street acc	i coo or won in locatou	276	9 Lin	da 1	LANE		2
	rry Co	Loux						
RR#, St. Address, Box # : 21	c9 -	Da Hama				of Agriculture, [Division of W	ater Resource
City, State, ZIP Code : S	alune,	Kanas		6740	Applic Applic	ation Number:		
LOCATE WELL'S LOCATION WITH 4	DEPTH OF CO	MPLETED WELL	58/2	. ft. ELEVA	TION:	12.4.3		
AN "X" IN SECTION BOX:	epth(s) Groundwa	ater Encountered 1	19	ft. 2	<u>.</u>	ft. 3		
;		VATER LEVEL (.						
NW NE	Pump t	est data: Well water	was 2	🗅 ft. at	fter	hours pu	mping	/. 5 gpn
	st. Yield 🎸	gpm: Well water	was	ft. af	fter	hours pu	mping	gpr
$W = \begin{bmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \end{bmatrix} E \begin{bmatrix} B \\ V \end{bmatrix}$	ore Hole Diamete	er % 1/2 in. to	3 .%				. to	8/2_1
	VELL WATER TO		Public wate		8 Air condition		Injection well	
sw X - se	1 Domestic					12		
	2 Irrigation					well		
	/as a chemical/ba	cteriological sample sul	bmitted to De			` .	*	
	nitted					ected? Yes		
TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concre			JOINTS: Glued	/	mpea
1 Steel 3 RMP (SR)		6 Asbestos-Cement		specify below	,		ed	
OPVC 4 ABS		7 Fiberglass					aded	
Slank casing diameter	10 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	ft., Dia						
Casing height above land surface		n., weight / . (2)		10s./1				. 20
TYPE OF SCREEN OR PERFORATION		. Fibereless		-		Asbestos-ceme		
1 Steel 3 Stainless s		5 Fiberglass		P (SR)		Other (specify)		
2 Brass 4 Galvanized CREEN OR PERFORATION OPENINGS		6 Concrete tile	9 ABS wrapped	•	(8) aw cut	None used (op	11 None (d	nen hole)
1 Continuous slot 3 Mill		6 Wire wr	• •		9 Drilled ho	loe	II NORG (C	pen noie)
	nahad	7 Toron o			10 Other /or	ooih ()		
SCREEN-PERFORATED INTERVALS:	From	8.1 ft. to	58%	tt From	n	ft t	0	
	From					ft. to		
GRAVEL PACK INTERVALS:		ft. to	34	ft Fror	n 35	ft. t	58	2//2
_	From	ft. to		ft., Fror		ft. te		f
GROUT MATERIAL: 1 Neat cer	ment 2	Cement grout	_3 Bento	nite 4	Other			
Grout Intervals: Fromft.	. to	ft., From 3	. ⊬ ft. :	10	ft., Froi	n	ft. to	
What is the nearest source of possible co					tock pens		bandoned wa	
1 Septic tank 4 Lateral	lines	7 Pit privy		11 Fuel:	storage	15 O	il well/Gas w	ell
2 Sewer lines 5 Cess p	ool	8 Sewage lagoo	n	12 Fertili	zer storage	16 O	ther (specify	below)
3 Watertight sewer lines 6 Seepag		9 Feedyard		13 Insec	ticide storage			
	1251		,	How mar	ny feet?	25		
FROM TO	LITHOLOGIC LO	OG	FROM	то		PLUGGING II	NTERVALS	<u> </u>
o' 3' Fill	dint							
	501,L							
6' 36' Brown	clay							
36' 39' Brow		+ LCALIB						
36, 39, Bion	in cla	y +SAND						
39' 58%	Yea							
39' 58% med.	m tol	44250						,
34.0	m to C	140 T						
	B 61.0	(ve)						
							,	
CONTRACTORIS OR LANDOWNERS	CERTIFICATIO	N. This water	A	tod (0) ====	notrusted a:	(2) physical	for my jurian	iction and
CONTRACTOR'S OR LANDOWNER'S	CEHTIFICATION							
ompleted on (mo/day/year)	273					e best of my kno		Dellet, Kansa
Vater Well Contractor's License No	0.00	This Water Wel		-	- M	1	0	1
inder the business name of	D Wee	- AJ		by (signat		wew	Hou	The same of the sa
INSTRUCTIONS: Use typewriter or ball point per of Health and Environment, Bureau of Water, To								s Department