		WA	TER WELL F	RECORD	Form WWC	-5 KSA 82	2a-1212 ID	No					
1 LOCATION OF WATER WELL: Fraction				Sec			Towns	ship Number					
				¼ SE		E 14	10	<u> </u>	14 s	R	3	K ⁄W	
1		n from nearest t	-				-						
1/4	mile '	West of					oad						
2 WATER	WELL OW			ey Cor	crete,	Inc.							
RR#, St. A	ddress, Bo		Cole					Board	of Agriculture,	Division of	Water	Resources	
City, State,			dsborg,		7456				ation Number:				
3 LOCATE	WELL'S LC	CATION WITH											
AN "X" I	N SECTIO	N BOX:							ft. 3				
	<u>N</u>								on mo/day/yr				
†	i i	_ i							hours				
	- NW -	NE Est. Yield 100gpm: Well water was 61ft. after 1./ 2 hours pumping 1.00gpm											
		Bore Hole Diameter1.2in. to8.5ft., andin. to											
№ W		E WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well **X Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering AND 12 Other (Specify below)											
ī	i	i	X Domes		edlot 6	Oil field water	r supply	9 Dewaterin	g 7770 12 (Other (Spe	cify bel	ow)	
	- SW -	SE	2 Irrigatio	n 4 in	dustrial 7	Domestic (law	n & garden) 1	U Monitoring	well 3 . 4 ?	CP4 1 11	(√)	• • • • • • •	
🗼	1 1	<u> </u>	Was a chemi	cal/bacteriok	ogical sample si	ubmitted to De	partment? Yes	s No.	X; If yes, i	mo/day/yrs	sample	e was sub-	
- -	' <u>I.</u> S		mitted				-		ected? Yes >		Ne		
5 TYPE O	F BLANK (CASING USED:			ght iron				VG JOINTS: Glu	ed. X	Clampe	∌d	
1 Steel		3 RMP (S	R)	6 Asbe	stos-Cement	9 Other	(specify belo	w)	Wel	ded			
<u>X</u> PVC		4 ABS	_	7 Fiber	glass				Thre	eaded			
Blank casi	ing diamete	_{er}	in. to	· 5	.ft., Di a	in	. to	. , ,ft., C	Dia	in. to .			
Casing he	ight above	land surface	12	in., weigl	ht	. 7.2	lbs.	/ft. Wall thick	kness or gauge I	No	3.	32	
_		OR PERFORA				% P∀			0 Asbestos-cen				
1 Steel 3 Stainless steel				5 Fibe	5 Fiberglass 8 RMP (SR)				1 Other (specify)		. 	
2 Brass 4 Galvanized steel			6 Cond	rete tile	9 AB:	S	1	2 None used (o	pen hole)				
SCREEN	OR PERF	ORATION OPE				zed wrapped		8 Saw cu		11 Non	e (open	hole)	
	tinuous slot	_	lill slot			wrapped		9 Drilled					
	vered shutt		ley punched	<i>-</i> -		h cut	_	•	specify)				
SCREEN-	-PERFORA	TED INTERVA							ft.				
	GBAVEL B	ACK INTERÎA							ft.				
	GNAVELT	AOK IIVI EIIVA							ft.				
6 GROUT	MATERIA	L: 1 Neat o	rement	2 Cem	ent grout	X Rentor	nite 4	Other			<u>.</u>		
Grout Intervals: From								10 Livestock pens			14 Abandoned water well		
				HURE				11 Fuel storage			15 Oil well/Gas well		
			utuice_	8 Sewage lagoon			12 Fertilizer storage			16 Other (specify below)			
_				9 Feedyard									
3 Watertight sewer lines 6 Seepage pit Direction from well? Northeast					9 reedyald			How many feet? 100					
		Northea	IST	1.00	<u>-</u> .	I EDOM	TO	illy leet?	PLUGGING I	NTEDVAL			
FROM	то	-	LITHOLOGIC	LOG		FROM	10		PLUGGING I	NIERVAL	.5		
_0	8	Fill i				 	<u> </u>						
8	10	Topsoi											
_1.0	32	Gray (
32	65	Fine S											
65	85		k Grave	<u> </u>									
	85_	Red_Sl	<u>nale</u>										
		ļ				- -							
		 -											
	<u> </u>	<u> </u>			-								
		 					ļ <u> </u>						
					•								
									or (3) plugged ui				
									the best of my k			ef. Kansas	
Water Well	Contractor						as completed	on (mo/day/	yr)	,10/00			
under the b	ousiness na	me of P	eterson	Irrig	ation,	Inc.	by (s	ignature)	n.l. W	to.			
					 				مور مور	everes			