			TER WELL REC	CORD	Form WW0	C-5 KSA 8	32a-1212 IE			
1 LOCATION	OF WA	TER WELL:	Fraction			Se	ction Numbe	r Township Nu	mber	Range Number
County:	Salin	e	NE ¼	SE	½ SE	S 1/4	11	т 14	S	R 3 X€/W
Distance and	direction	from nearest to	own or city stree	t addres:	s of well if lo	cated within o	ity?	· · ·		-
Tn c	ity 7	imits _	300 W. A	sh.	Salina	KS				
2 WATER W	ELL OW	VER: Sali	ine CoC	itv	Buildir	og Anthe	ritu			
RR#. St. Add			Box 504				, , , , , , , , , , , , , , , , , , ,	Roard of Agri	culture I	Division of Water Resources
City, State, ZI	•			-	2-5040	1011		Application N		Simple of Trace Treatment
						6.1	# ELEV	• •		
AN "X" IN										
AN X IN	N N	BUX:								2/1.6/02
Ā		1								
	!	1								pumping gpm
N	- NW NE - Est. Yield .300gpm: Well water wasft. after hours pumping									
	i l	Bore Hole Diameter 20in. toft., andin. toft.								
■ W		E WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well								
Ī	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial X Domestic (lawn & garden) 10 Monitoring well									
	w – –	SE	2 Irrigation	4 Inc	dustrial 🕻	Domestic (lav	vn & garden)	10 Monitoring well		
		_ ! * }	Mac a chemical/	haatoriolo	udical cample o	submitted to De	nartment? Ve	ne No X	· If you r	no/day/yrs sample was sub-
<u> </u>	<u> </u>		mitted	DACIGNOIL	igical sample :	sabilitied to De	•	er Well Disinfected?	-	X No
5 TYPE OF	BLANK C	ASING USED:	milled	5 Wrou	ght iron	8 Conc	rete tile			ed. X Clamped
1 Steel		3 RMP (SI	R)		stos-Cement		(specify bel			ded
X2 PVC		4 ABS	''	7 Fiber			• • •			eaded
					~		-			
										in. to
Casing heigh	it above l	and surface	!.4 i	in., weigh	ìt			s./ft. Walf thickness or	r gauge N	4o . 332
TYPE OF S	CREEN C	OR PERFORAT	ΓΙΟΝ MATERIAL			X P\		10 Asbe		
)	
2 Brass		4 Galvaniz		6 Conci	rete tile	9 AE	is .	12 None	used (o	pen hole)
l		RATION OPE				uzed wrapped		8 Saw cut		11 None (open hole)
1 Continu		_	ill slot			e wrapped		9 Drilled holes		•
2 Louver			ey punched			ch cut				
SCREEN-PE	ERFORAT	red interval								toft.
			From	25	ft. to .	64	ft., Fro	m <i></i>	ft. 1	to. ,
GF	AVEL PA	ACK INTERVAL								to
6 GROUT M					ent grout					
Grout Interv	als: Fro	m . 4	ft. to	lf	t., From		. to	ft., From		ft. to
What is the nearest source of possible contamination:				า:				10 Livestock pens		Abandoned water well
1 Septic tank 4 Lateral lines				7 Pit priv	у	11 Fue	11 Fuel storage		15 Oil well/Gas well	
2 Sewer lines 5 Cess pool				8 Sewage lagoon			12 Fertilizer storage		Other (specify below)	
X Watertight sewer lines 6 Seepage pit				9 Feedyard			13 Insecticide storage			
Direction from			•		•			any feet? 300		
FROM	ТО		LITHOLOGIC LO	OG.		FROM	TO		GING II	NTERVALS
l						1113111	1			
0	2	Topsoi				-	+ 1			
	12		brown				 			
	34		silty, b							
	64		fine to	mea1	um		 			
64	65	Shale,	, gray							
				,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,						
										· · · · · · · · · · · · · · · · · · ·
							 			
7 CONTRACT	TOP'S O	P I ANDOMNE	R'S CERTIFICAT	ION: Thi	ie water well	wae #1 cons	ructed (2) ==	constructed or (2) of	naged +-	der my jurisdiction and was
_			2/19/02							
completed on									2/21	owledge and belief. Kansas
l			<u>1</u>						٠٠٠.	46
under the bus	iness nan	ne of Fele	erson Irr	-yar	TOIL, II		by (:	signature)	161	2