LOCATE WELL OWNET   Township Number   Range Number   Township Number   Township Number   Range Number   Township Number   Township Number   Township Number   Range Number   Township	Resource fit gp gp gp low) hole)
Distance and direction from nearest town or city street address of welly it located within city?    WATER WELL OWNER:   Tell   Elan   Pelan	Plesourd from the second from
WATER WELL OWNER:  RR#, St. Address, Box #: 3616, Brey Application Number:  LOCATE WELLS LOCATION WITH A DEPTH OF COMPLETED WELL. 53 / 2 ft. ELEVATION: 7.2 9/ 1.3 ft. ELEVATION: 7.3 ft. Diowidal surface measured on moidaly/yr compound on moidal/yr compound on moidal/	gp gp low)
Board of Agriculture, Division of Water Rapplication Number:  LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  WELL'S STATIC WATER LEVEL. \$2. ft. 2. ft. 3.  WELL'S STATIC WATER LEVEL. \$2. ft. 2. ft. 3.  WELL'S STATIC WATER LEVEL. \$2. ft. 4. ft. 2. ft. 3.  WELL'S STATIC WATER LEVEL. \$2. ft. 4. ft. 2. ft. 3.  WELL'S STATIC WATER LEVEL. \$2. ft. 4. ft. 2. ft. 3.  WELL'S STATIC WATER LEVEL. \$2. ft. 4. ft. 2. ft. 3.  WELL'S STATIC WATER LEVEL. \$2. ft. 4. ft. 2. ft. 3.  WELL'S STATIC WATER LEVEL. \$2. ft. 4. fter four pumping. \$5. ft. 4. fter four four four four four four four fou	gp gp low)
Application Number:  LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX.  WELL'S STATIC WATER LEVEL	gp gp low)
Depth(s) Groundwater Encountered 1. 2 ft. 2. ft. 3.  WELL'S STATIC WATER LEVEL 2 ft. below land surface measured on mo/day/yr 6. 7. 7.  Pump test data: Well water was 2. 2. 4t. after 1. hours pumping 2. 5.  Pump test data: Well water was 2. 4t. after 2. hours pumping 2. 5.  Bore Hole Diameter 3. 2. in. to 3. 5. Public water supply 8. Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6. Oil field water supply 9. Dewatering 12. Other (Specify below 2 Irrigation 4 Industrial 2 Jawn and garden only 10 Monitoring well 3. Stell	gp gp low)
Purpo test data: Well water was 22/4ft. after 1/2 hours pumping 1/2 by 1/4 by 1	Johnstein Spiriter Sp
WELL WATER TO BE USED AS:  SW - SW - SE - SW - SE - SW - SE - SW - SW	low)
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below 2 Irrigation 4 Industrial 2 Jawn and garden only 10 Monitoring well was a chemical/bacteriological sample submitted to Department? Yes	hole)
1 Domestic 2 Irrigation 4 Industrial 2 awn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes	hole)
2 Irrigation 4 Industrial Jawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes	hole)
Was a chemical/bacteriological sample submitted to Department? Yes	hole)
TYPE OF BLANK CASING USED:  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  2 PVC 4 ABS 7 Fiberglass Threaded.  Iank casing diameter 5 in to 43 ft., Dia in to asing height above land surface 7 in, weight 15 Fiberglass 8 RMP (SR)  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)  1 Continuous slot 3 Mill slot 6 Wire wrapped 8 Saw cut 11 None (open hole)  2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  CREEN-PERFORATED INTERVALS: From 15 to 5 3 1/2 ft., From 15 to 5 1/2 ft., From 15	hole)
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  2 PVC 4 ABS 7 Fiberglass Threaded.  lank casing diameter 5 in to 43 ft., Dia in to ft., Dia in to asing height above land surface 7 in, weight 6 O B lbs./ft. Wall thickness or gauge No. SPR 2 for SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  CREEN-PERFORATED INTERVALS: From ft. to ft., From ft.,	hole)
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded.  Iank casing diameter 5 in to 43 ft., Dia in to ft., Dia in to sasing height above land surface 7 in, weight 6 Concrete tile 9 ABS 12 None used (open hole)  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  2 Louvered shutter 4 Key punched CREEN-PERFORATED INTERVALS: From ft. to ft., From ft.	hole)
lank casing diameter 5 in to 43 ft., Dia in to	hole)
lank casing diameter 5 in to 43 ft., Dia in to	hole)
asing height above land surface	hole)
PPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	hole)
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	hole)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 aw cut 11 None (open hole)  1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  2 Louvered shutter 4 Key punched  CREEN-PERFORATED INTERVALS: From. 43/2 ft., From ft. to ft., From ft., Fr	hole)
CREEN OR PERFORATION OPENINGS ARE:   5   Gauzed wrapped   8   Saw cut   11   None (open he of the property o	
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  CREEN-PERFORATED INTERVALS: From #1. to 53/2 ft., From ft. to ft., From ft.,	
2 Louvered shutter	
CREEN-PERFORATED INTERVALS:         From.         43/2 ft. to         53/2 ft., From.         ft. to           From.         ft. to         ft., From.         ft. to           GRAVEL PACK INTERVALS:         From.         2.3 ft. to         53/2 ft., From.         ft. from.           From.         ft. to         ft., From.         ft. to           GROUT MATERIAL:         Dieat cement         2 Cement grout         3 Bentonite         4 Other	
From         ft. to         ft., From         ft. to           GROUT MATERIAL:         1 leat cement         2 Cement grout         3 Bentonite         4 Other	
From         ft. to         ft., From         ft. to           GROUT MATERIAL:         1 leat cement         2 Cement grout         3 Bentonite         4 Other	
GROUT MATERIAL: 2 Cement grout 3 Bentonite 4 Other	
rout Intervals: Fromft. to	
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	w)
(3) Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	•,
irection from well? NONTH How many feet? 50	
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
0'2' FILL dirt	
21 31 800 Soil	
7' 16' Brn clay,	
16' 17' Fine JANG, +Clay MIX	
17 76' Brown clar	
36/53/2 Medium To Coarse	
JANG & graveL	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction a	
	and wa
mpleted on (mo/day/year) (C-43-V) and this record is true to the best of my knowledge and belief	