

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Saline</u>		<u>NE 1/4 SW 1/4 NE 1/4</u>	<u>36</u>	T <u>14</u> S	R <u>3</u> EW
Distance and direction from nearest town or city street address of well if located within city? <u>2523 Edwards, Salina Ks</u>					
2 WATER WELL OWNER: <u>Dan Reinsch</u>		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: <u>2523 Edwards</u>		Application Number:			
City, State, ZIP Code: <u>Salina, Ks.</u>					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>55</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield <u>50</u> gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>9</u> in. to <u>30</u> ft., and <u>8</u> in. to <u>60</u> ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 10 Monitoring well 12 Other (Specify below)			
		Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped			
1 Steel 3 RMP (SR)		Welded			
2 PVC 4 ABS		Threaded			
Blank casing diameter <u>5</u> in. to <u>40</u> ft., Dia		Casing height above land surface <u>12</u> in., weight <u>160</u> lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From <u>55</u> ft. to <u>40</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>60</u> ft. to <u>23</u> ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From <u>23</u> ft. to <u>3</u> ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		How many feet? <u>60</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	7	Clay - brown, gray, silty			
7	9	Clay - brown, v. stiff			
9	27	Clay - brown, silty			
27	36	Sand and Gravel			
36	40	Sand and Gravel w/ gray clay lenses			
40	55	Sand and Gravel			
55	60	Sand and Gravel w/dk gray clay lenses			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>11/23/02</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>527</u> This Water Well Record was completed on (mo/day/yr) <u>11/26/02</u> under the business name of <u>GeoCore Inc.</u> by (signature) <u>Dan Reinsch</u>					