

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Saline	SE ¼ SE ¼ SE ¼	23	T 14 S	R 03

Distance and direction from nearest town or city street address of well if located within city?

1700 S. 9th Street

2 WATER WELL OWNER:	Moo To You, Inc.	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	PO Box 4119	Application Number:
City, State, ZIP Code :	Wichita, KS 67204-4119	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	40 ft. ELEVATION:	1234.36 (TOC)	
	Depth(s) Groundwater Encountered	1 33 ft. 2 ft. 3 ft.		
	WELL'S STATIC WATER LEVEL	32.28 ft. below land surface measured on mo/day/yr	10-13-04	
	Pump test data:	Well water was	ft. after	hours pumping
	Est. Yield	gpm: Well water was	ft. after	hours pumping
	Bore Hole Diameter	8.5 in. to 40 ft. and in. to		
WELL WATER TO BE USED AS:	5 Public water supply	8 Air conditioning	11 Injection well	
1 Domestic	3 Feed lot	6 Oil field water supply	9 Dewatering	
2 Irrigation	4 Industrial	7 Lawn and garden (domestic)	10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted				
Water Well Disinfected? Yes No X				

5 TYPE OF BLANK CASING USED:	5 Wrought Iron	8 Concrete tile	CASING JOINTS: Glued	Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	4 ABS	7 Fiberglass		Threaded
Blank casing diameter	2 in. to 15 ft., Dia			Flush
Casing height above land surface	Flushmount in., weight	0.703 lbs./ft. Wall thickness or gauge No.	Sch. 40	
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:				
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes	10 Other (specify)
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:				
From	15 ft. to	40 ft. From		
From				
GRAVEL PACK INTERVALS:				
From	13 ft. to	40 ft. From		
From				

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other	Bentonite Grout
Grout intervals	From 0.5 ft. to 12 ft. From 12 ft. to 13 ft. From				
What is the nearest source of possible contamination:					
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/ Gas well	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)	
Direction from well? How many feet?					

FROM	TO	CODE	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5		Concrete			
0.5	3		Fill			
3	20		Clay, silty, mod to high plasticity, stiff, brown			
20	22		Sand			
22	30		Clayey Silt, low plasticity, soft, gray			
30	40		Sand, grading to gravel with occasional clay stringer			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was	(1) constructed	(2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr)	11-22-04	and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No.	531	This Water Well Record was completed on (mo/day/yr)	11-23-04	
under the business name of	Geotechnical Services, Inc.	by (signature)		

INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.