

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number	
County: Saline		SW ¼ SW ¼ SW ¼	1	T 14 S	R 3 E	
Distance and direction from nearest town or city street address of well if located within city? 900 N. Ninth St., Salina						
2 WATER WELL OWNER: Reimold Properties, Inc. RR#, St. Address, Box # : Attn: Bill Reimold City, State, ZIP Code : P.O. Box 1302 Salina, KS 67402						
Board of Agriculture, Division of Water Resources Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N - - NW - - NE - - W - - SW - - SE - - S		4 DEPTH OF COMPLETED WELL 39 ft. ELEVATION: 1219.88 Depth(s) Groundwater Encountered 1 ~ 28 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 27.33 ft. below land surface measured on mo/day/yr 01/13/05 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Domestic (lawn & garden) 10 Monitoring well				
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yrs sample was submitted _____ Water Well Disinfected? Yes No						
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter in. to 39 ft. Dia in. to ft. Dia in. to ft. Threading: Threaded X Casing height above land surface - 4.08 in., weight lbs./ft. Wall thickness or gauge No Sch 40 PVC TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 4 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 3 Torch cut 10 Other (specify) ft.						
SCREEN-PERFORATED INTERVALS: From 19 ft. to 29 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 17 ft. to 40 ft. From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals: From 1 ft. to 17 ft. From ft. to ft. From ft. to ft.						
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? How many feet? Rust Site						
		LITHOLOGIC LOG	PLUGGING INTERVALS			
FROM	TO		FROM	TO		
0	0.5	Concrete				
0.5	13	Clay, dry				
13	20	Silty sand, very finegrained, dry				
20	35	Clay moist high odor				
35	40	Sand, fine to medium graind, high odor				
			MW 20			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 01/13/05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 594 This Water Well Record was completed on (mo/day/yr) 3/3/05 under the business name of Corcoran Great Plains, Inc. by (signature)						