

1 LOCATION OF WATER WELL: County: <u>Saline</u>	Fraction <u>SW 1/4 SW 1/4 SW 1/4</u>	Section Number <u>1</u>	Township Number <u>T 14 S</u>	Range Number <u>R 3</u> <small>EW</small>	
Distance and direction from nearest town or city street address of well, if located within city? <u>900 N. Ninth St., Salina</u>					
2 WATER WELL OWNER: <u>Reimold Properties, Inc.</u> RR#, St. Address, Box # : <u>Attn: Bill Reimold</u> City, State, ZIP Code : <u>P.O. Box 1302 Salina, KS 67402</u>					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>45</u> ft. ELEVATION: <u>1220.08</u>			
		Depth(s) Groundwater Encountered <u>1 ~28</u> ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL <u>NM</u> ft. below land surface measured on mo/day/yr <u>NM</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well <u>Air Spurge Observation</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>(X)</u>			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 <u>PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>2</u> in. to <u>45</u> ft., Dia in. to ft., Dia in. to ft. Casing height above land surface <u>-3.16</u> in., weight lbs./ft. Wall thickness or gauge No. <u>Sch 40 PVC</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 7 <u>PVC</u> 10 Asbestos-Cement 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 2 <u>Mill slot</u> 5 Guazed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) ft.					
SCREEN-PERFORATED INTERVALS: From <u>42.5</u> ft. to <u>45</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>40</u> ft. to <u>45</u> ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 <u>Bentonite</u> 4 Other					
Grout Intervals: From <u>1</u> ft. to <u>40</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) <u>16 Other (specify below) Fuel Silo</u>					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Concrete			
0.5	12	Fill			
12	15	Sand, dry, high order, medium grained			
15	22	Silty sand, very fine grained, high order, dry			
22	34.5	Clay, moist, high order			
34.5	45	Sand, wet, fine to medium grained, high order			
					ASOBW 1
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>01/13/05</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. <u>394</u> This Water Well Record was completed on (mo/day/yr) <u>3/3/05</u> under the business name of <u>Coronado Great Plains, Inc.</u> by (signature) <u>Michael E. J. J. J.</u>					