

[1] LOCATION OF WATER WELL:		Fraction	Township Number	Range Number		
County: SALINE		N ¼ E ¼ NE ¼	Section Number 36 T 14 S	R 3W E/W		
Distance and direction from nearest town or city street address of well if located within city? 941 TWIN OAKS						
[2] WATER WELL OWNER: CORENA HELVEY						
RR#, St. Address, Box # : 941 TWIN OAKS			Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : SALINA, KS. 67401			Application Number:			
[3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		[4] DEPTH OF COMPLETED WELL 53 ft. ELEVATION: 1241				
<p>A square divided by horizontal and vertical lines into four smaller squares representing sections. The top-left quadrant contains '-NW-', top-right '-NE- X -', bottom-left '-SW-', and bottom-right '-SE-'.</p>		Depth(s) Groundwater Encountered 1 20 ft. 2 ft. WELL'S STATIC WATER LEVEL .20 ft. below land surface measured on mo/day/yr 4-05-05 Pump test data: Well water was 21 ft. after 1 hours pumping 20 gpm Est. Yield .75 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well, Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yrs sample was submitted _____ Water Well Disinfected? Yes <u>X</u> No _____.				
[5] TYPE OF BLANK CASING USED:						
1 Steel 2 PVC Blank casing diameter 5 in. to 43 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 26		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) _____ CASING JOINTS: Glued <u>X</u> Clamped Welded Threaded				
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 2 Louvered shutter 3 Mill slot025 4 Key punched		5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) ft. 11 None (open hole)				
SCREEN-PERFORATED INTERVALS: From 43 ft. to 53 ft., From ft. to ft., From ft. to ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From 21 ft. to 53 ft., From ft. to ft., From ft. to ft., From ft. to ft.						
[6] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals: From 0 ft. to 21 ft., From ft. to ft., From ft. to ft., From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank 2 Sewer lines 3 Watertight sewer lines Direction from well? SOUTH		4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage How many feet? 40				
FROM		TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0		3	FILL DIRT			
3		18	CLAY GRAY FIRM			
18		21	CLAY TAN			
21		53	SAND FINE TO MED. TAN			
53			CLAY GRAY HARD			
[7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>4-05-05</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. <u>388</u> . This Water Well Record was completed on (mo/day/yr) <u>4-05-05</u> under the business name of <u>PESTINGER PUMP SERVICE</u> by (signature) <i>Dan Pestinger</i> .						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY AND PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.						