

SLMW1

| | | | | |
|---------------------------|-----------------------------|----------------|-----------------|--------------|
| 1 LOCATION OF WATER WELL: | Fraction | Section Number | Township Number | Range Number |
| County: <u>SALINE</u> | <u>NW 1/4 NE 1/4 SW 1/4</u> | <u>12</u> | <u>T 14 S</u> | <u>R 3 E</u> |


Distance and direction from nearest town or city street address of well if located within city?

WEST SIDE OF N 3RD ST, 1 BLK SOUTH OF E. NORTH STREET2 WATER WELL OWNER: KANSAS GAS SERVICERR#, St. Address, Box #: 340 E 1ST STCity, State, ZIP Code: TOPEKA, KS 66601

Board of Agriculture, Division of Water Resources

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 1228.15Depth(s) Groundwater Encountered 1. 32.50 ft. 2. 32.50 ft. 3. 32.50 ft.WELL'S STATIC WATER LEVEL: 32.50 ft. below land surface measured on mo/day/yr 8.25.05Pump test data: Well water was 32.50 ft. after 32.50 hours pumping 32.50 gpmEst. Yield 32.50 gpm: Well water was 32.50 ft. after 32.50 hours pumping 32.50 gpmBore Hole Diameter: 8 in. to 40 in. to 40 in. to 40 in.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes Yes No No; If yes, mo/day/yr sample was submitted To be submittedWater Well Disinfected? Yes Yes No No

5 TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Glued Clamped Clamped2 Brass 4 Galvanized steel 6 Asbestos-Cement 9 Other (specify below) Welded WeldedBlank casing diameter 2 in. to 25 in. Dia 25 in. to 25 in. Dia 25 in. to 25 in. Dia 25 in. to 25 in. DiaCasing height above land surface 0 in., weight SC440 lbs./ft. Wall thickness or gauge No. SC440

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 40 ft. to 25 ft. From 40 ft. to 25 ft. From 40 ft. to 25 ft. From 40 ft. to 25 ft.GRAVEL PACK INTERVALS: From 40 ft. to 23 ft. From 40 ft. to 23 ft. From 40 ft. to 23 ft. From 40 ft. to 23 ft.From 40 ft. to 23 ft. From 40 ft. to 23 ft. From 40 ft. to 23 ft. From 40 ft. to 23 ft.From 40 ft. to 23 ft. From 40 ft. to 23 ft. From 40 ft. to 23 ft. From 40 ft. to 23 ft.

6 GROUT MATERIAL:

1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 23 ft. to 1 ft. From 23 ft. to 1 ft. From 23 ft. to 1 ft. From 23 ft. to 1 ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

Direction from well? 100How many feet? 100

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 4 Dravel

4 12 Silt/clay

12 21 Sandy silt

21 29.5 Silt/clay-wet

29.5 30.5 Sand-wet

30.5 40.0 Clay-wet

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-21-05 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's License No. 529This Water Well Record was completed on (mo/day/yr) 7-21-05under the business name of Geotechnology, Inc by (signature) [Signature]