

1
LOCATION OF WATER WELL:
County:
Saline
Fraction:
SW
NW
SE
Section Number:
12
Township Number:
T
14
S
Range Number:
R
03
W

Distance and direction from nearest town or city street address of well if located within city?
338 N. Front St., Salina

2
WATER WELL OWNER:
KDHE
RR#, St. Address, Box #:
1000 SW Jackson Ste. 410
City, State, ZIP Code:
Topeka, KS 66612
Board of Agriculture, Division of Water Resources
Application Number:

3
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4
DEPTH OF COMPLETED WELL:
48 ft.
ELEVATION:
Depth(s) Groundwater Encountered:
1 ft.
2 ft.
3 ft.
WELL'S STATIC WATER LEVEL:
34.95 ft. below land surface measured on mo/day/yr
10-13-05
Pump test data:
Well water was
ft. after
hours pumping
gpm
Est. Yield:
gpm
Well water was
ft. after
hours pumping
gpm
Bore Hole Diameter:
8.5 in. to
48 ft. and
in. to
ft.
WELL WATER TO BE USED AS:
5 Public water supply
8 Air conditioning
11 Injection well
1 Domestic
3 Feed lot
6 Oil field water supply
9 Dewatering
12 Other (Specify below)
2 Irrigation
4 Industrial
7 Lawn and garden (domestic)
10 Monitoring well
Was a chemical/bacteriological sample submitted to Department?
Yes
No
X
If yes, mo/day/yr sample was submitted
Water Well Disinfected?
Yes
No
X

5
TYPE OF BLANK CASING USED:
1 Steel
2 PVC
3 RMP (SR)
4 ABS
5 Wrought Iron
6 Asbestos-Cement
7 Fiberglass
8 Concrete tile
9 Other (specify below)
CASING JOINTS:
Glued
Clamped
Welded
Threaded
Flush
Blank casing diameter:
2 in. to
38 ft., Dia
in. to
ft., Dia
in. to
ft.
Casing height above land surface:
Flushmount
in., weight:
0.703 lbs./ft.
Wall thickness or gauge No.:
Sch. 40
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel
2 Brass
3 Stainless steel
4 Galvanized steel
5 Fiberglass
6 Concrete tile
7 PVC
8 RMP (SR)
9 ABS
10 Asbestos-cement
11 Other (specify)
12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot
2 Louvered shutter
3 Mill slot
4 Key punched
5 Gauzed wrapped
6 Wire wrapped
7 Torch cut
8 Saw cut
9 Drilled holes
10 Other (specify)
11 None (open hole)
SCREEN-PERFORATED INTERVALS:
From
38 ft. to
48 ft.
From
ft. to
ft.
From
ft. to
ft.
GRAVEL PACK INTERVALS:
From
35 ft. to
48 ft.
From
ft. to
ft.
From
ft. to
ft.

6
GROUT MATERIAL:
1 Neat cement
2 Cement grout
3 Bentonite
4 Other
Grout Intervals:
From
0.5 ft. to
35 ft.
From
ft. to
ft.
From
ft. to
ft.
What is the nearest source of possible contamination:
1 Septic tank
2 Sewer lines
3 Watertight sewer lines
4 Lateral lines
5 Cess pool
6 Seepage pit
7 Pit privy
8 Sewage lagoon
9 Feedyard
10 Livestock pens
11 Fuel storage
12 Fertilizer storage
13 Insecticide storage
14 Abandoned water well
15 Oil well/ Gas well
16 Other (specify below)
Direction from well?
How many feet?

FROM
TO
CODE
LITHOLOGIC LOG
FROM
TO
PLUGGING INTERVALS

0
15
CL-ML
Silty Clay, mod plasticity, stiff, brown to light brown

15
25
ML
Silt, with clay, low plasticity, grading to very fine sand, light brown, alternating layers of silty clay with very fine grain sand

25
28
CL-ML
Silty Clay, mod to high plasticity, light brown to gray

28
48
SW
Sand, with gravel, well graded, size increasing with depth, pebbles

7
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:
This water well was
(1) constructed,
(2) reconstructed,
or
(3) plugged
under my jurisdiction and was completed on (mo/day/yr)
10-13-05
and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No.
531
This Water Well Record was completed on (mo/day/yr)
11-9-05
under the business name of
Geotechnical Services, Inc.
by (signature)

INSTRUCTIONS:
Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.