	WATER	WELL RECORD Form	n WWC-5 KS	A 82a-1212	ID No.	MW - 5
1 LOCATION OF WATER WELL:			1		•	Range Number
County: Saline	NW ¼	NE ¼ NW	1/4 23	<u> </u>	<b>14</b> 8	R 3 E/W
Distance and direction from nearest tow	n or city street addre	ess of well if located wit	hin city?			٠.
2 WATER WELL OWNER: Sunse	t Plaza Reality	Partners, Inc.				
RR#, St. Address, Box # : PO Bo				В	oard of Agriculture	, Division of Water Resources
City, State, ZIP Code : Kansa	s City, MO				pplication Number	
2 LOCATE WELL'S LOCATON WITH			25			
AN "X" IN SECTION BOX:	DEPTH OF CO	MPLETED WELL	35 f	t. ELEVATIO	)N:	
N N						ft. 3ft.
						o/day/yr
NWNE						ours pumpinggpm
® W E	Est. Yield	gpm: Well water v	vas	ft. afte	er ho	ours pumping gpm
-	Bore Hole Diamete	r <b>Ö</b> in to BEUSEDAS 5 Püt	Jic water sunnly	ft.aı	nd Air conditioning	in. to ft. 11 Injection well 12 Other (Specify below)
sw se	1 Domestic	3 Feed lot 6 Oil	field water supply	ly 9	Dewatering	12 Other (Specify below)
	2 Irrigation	4 Industrial 7 Lav	vn and garden (d	domestic) 1	0 Monitoring well	
S				rtment? Yes	No <b>X</b> I	f yes, mo/day/yr sample was
	submitted					es No X
5 TYPE OF BLANK CASING USED:		5 Wrought Iron				Glued Clamped
1 Steel 3 RMP (		6 Asbestos-Cement	9 Other (spec	cify below)		Welded
2 PVC 4 ABS		7 Fiberglass				Threaded X
Blank casing diameter 4	in. to 20	ft., Dia	in. to	ft.,	Dia	in, to ft.
Blank casing diameter 4 in. to 20 ft., Dia in. to ft.  Casing height above land surface 0 in., weight 2.071 lbs./ft. Wall thickness or gauge No237  TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)						
1 Steel 3 Stainle	ess steel	5 Fiberglass	8 RMF	2 2 (SR)	10 Aspestos-	cement acify)
2 Brass 4 Galva	nized steel	6 Concrete tile	9 ABS	5 ~	12 None used	d (open hole)
Saw cut 11 None (open noie)						
1 Continuous slot 3 2 Louvered shutter 4	Mill slot	6 Wire wi 7 Torch o		9	Drilled holes	
SCREEN-PERFORATED INTERVALS:				10	Other (specify)	A 4-
CONCENT EN OFFICE INTERVALS.						ft. toft.
GRAVEL PACK INTERVALS:	From 1	8 ft to	35	# From		ft. to ft.
	From	ft. to		ft From		ft. to ft.
6 GROUT MATERIAL: 1 Neat	cement 2 C	Cement grout	3 Bentonite	e 4.0	ther	11. 10
Grout Intervals From 0	ft. to 18	ft. From	ft. to	_ , 0	ft. From	ft. to ft.
What is the nearest source of possible	contamination:		10	) Livestock	pens 14	4 Abandoned water well
1 Septic tank	4 Lateral lines	7 Pit privy				5_Oil well/ Gas well
2 Sewer lines	5 Cess pool	8 Sewage la	agoon 12	? Fertilizer s	torage 1	Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Contaminated Site						
Direction from well?  FROM TO CODE	LITHOLO	GICTOG		w many feet?		NG INTERVALS
	ncrete	0.0 1.00	TIOW	-	FLUGGII	NO INTERVALO
1 15 Le	an Clay, Brow	n				
15 30 Le	an Clay, Light	Brown				
30 35 Le	an Clay w/ Sar	nd				
					1,014, 1,014, 1,014, 1	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was						
completed on (mo/day/yr) 10-21-05 and this record is true to the best of my knowledge and belief. Kansas						
Water Well Contractor's License No. under the business name of		554	This Water		was completed on	
under the business name of	Woofte	r Pump & Well, Ir	10	by (sig	nature) (hall	Colorto
INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						