	WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No MW - 8
1 LOCATION OF WATER WELL:	
County: Saline	NW 1/2 NE 1/4 NW 1/4 23 T 14 S R 3 EM
Distance and direction from nearest toy	n or city street address of well if located within city?
2 WATER WELL OWNER: Sunse	t Plaza Reality Partners, Inc.
RR#, St. Address, Box # : PO Bo	
City, State, ZIP Code : Kansa	s City, MO Application Number:
3 LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL 35 ft. ELEVATION:
N N N OE OTHER BOX.	Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.
t XIII	
NWNE	WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr
	Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm
₽ W E	Bore Hole Diameter 8 in to 35 ft and in to ft.
17	Bore Hole Diameter 8 in. to 35 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
SW SE	
 	2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well
S	Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X
5 TYPE OF BLANK CASING USED:	
	(SR) 6 Asbestos-Cement 9 Other (specify below) Welded
PVC 4 ABS	· · · · · · · · · · · · · · · · · · ·
Blank casing diameter 4	in to 20 ft Dia in to ft Dia in to ft
Casing height above land surface	0 in., weight 2.071 lbs./ft. Wall thickness or gauge No237
TYPE OF SCREEN OR PERFORATION	N MATERIAL: 10 Asbestos-cement
1 Steel 3 Stainl	0 in., weight 2.071 lbs./ft. Wall thickness or gauge No237 NMATERIAL: 10 Asbestos-cement ess steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) inized steel 6 Concrete tile 9 ABS 12 None used (open hole)
2 Brass 4 Galva SCREEN OR PERFORATION OPENII 1 Continuous slot 3	NGS ARE: 5 Gauzed wrapped 12 None used (open hole) 12 None used (open hole) 2 Saw cut 11 None (open hole)
1 Continuous slot 3	Mill slot 6 Wire wrapped 9 Drilled holes
I	Key punched 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS	***************************************
GRAVEL PACK INTERVALS:	From ft. to ft. From ft. to ft. From 18 ft. to 35 ft. From ft. to ft.
SINVEL FACK INTERVALS.	From ft. to ft. From ft. to ft.
6 GROUT MATERIAL: 1 Neat	cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals From 0 ft. to 18 ft. From ft. to ft. From ft. to ft.	
What is the nearest source of possible	contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank	4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well
2 Sewer lines 3 Watertight sewer lines	5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 6 Seepage pit 9 Feedyard 13 Insecticide storage Contaminated Site
Direction from well?	6 Seepage pit 9 Feedyard 13 Insecticide storage Contaminated Site How many feet?
FROM TO CODE	LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
	sphalt Section 10 - 10 - 10 - 10 - 10 - 10 - 10 - 10
	Ity Lean Clay, Medium Brown
10 20 Si 20 35 Si	Ity Lean Clay, Dark Brown Ity Lean Clay, Reddish Brown
	is Evan Viay, Neddish Brown
7 CONTRACTOR'S OR LANDOWNE	R'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was
completed on (mo/day/yr) 10-18-05 and this record is true to the best of my knowledge and belief. Kansas	
Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 12-20-05	
under the business name of Woofter Pump & Well. Inc by (signature)	
INSTRUCTIONS: Please fill in blan Jackson St., Ste. 420, Toneka, Kans	ks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W
Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one to your records.	