

1
LOCATION OF WATER WELL:

County:
Saline

Fraction
SE
¼
SW
¼
NW
¼

Section Number
12

Township Number
T
14
S

Range Number
R
03
W

Distance and direction from nearest town or city street address of well if located within city?
501 N. Front St. (40 ft. east of east wall, 23 ft north of fence)

2
WATER WELL OWNER:
Kansas Department of Health & Environment

RR#, St. Address, Box #
1000 SW Jackson Ste 410

City, State, ZIP Code
Topeka, KS 66612-1367

Board of Agriculture, Division of Water Resources

Application Number:

3
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4
DEPTH OF COMPLETED WELL
43
ft. ELEVATION:

Depth(s) Groundwater Encountered
1
31
ft. 2
ft. 3
ft.

WELL'S STATIC WATER LEVEL
ft. below land surface measured on mo/day/yr

Pump test data: Well water was
ft. after
hours pumping
gpm

Est. Yield
gpm: Well water was
ft. after
hours pumping
gpm

Bore Hole Diameter
8.5
in. to
43
ft. and
in. to
ft.

WELL WATER TO BE USED AS:
5 Public water supply
8 Air conditioning
11 Injection well
1 Domestic
3 Feed lot
6 Oil field water supply
9 Dewatering
12 Other (Specify below)
2 Irrigation
4 Industrial
7 Lawn and garden (domestic)
10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes
No
X
If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes
No
X

5
TYPE OF BLANK CASING USED:

1 Steel
3 RMP (SR)
5 Wrought Iron
8 Concrete tile
CASING JOINTS: Glued
Clamped

2 PVC
4 ABS
6 Asbestos-Cement
9 Other (specify below)
Welded

7 Fiberglass
Threaded
Flush

Blank casing diameter
2
in. to
33
ft. Dia
in. to
ft. Dia
in. to
ft.

Casing height above land surface
Flushmount
in., weight
0.703
lbs./ft. Wall thickness or gauge No.
Sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel
3 Stainless steel
5 Fiberglass
8 RMP (SR)
11 Other (specify)
2 Brass
4 Galvanized steel
6 Concrete tile
9 ABS
12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot
3 Mill slot
5 Gauzed wrapped
8 Saw cut
11 None (open hole)
2 Louvered shutter
4 Key punched
6 Wire wrapped
9 Drilled holes
10 Other (specify)
7 Torch cut

SCREEN-PERFORATED INTERVALS:

From
33
ft. to
43
ft. From
ft. to
ft.

GRAVEL PACK INTERVALS:

From
31
ft. to
43
ft. From
ft. to
ft.

From
ft. to
ft. From
ft. to
ft.

6
GROUT MATERIAL:

1 Neat cement
2 Cement grout
3 Bentonite
4 Other

Grout Intervals
From
1
ft. to
31
ft. From
ft. to
ft. From
ft. to
ft.

What is the nearest source of possible contamination:

1 Septic tank
4 Lateral lines
7 Pit privy
10 Livestock pens
14 Abandoned water well
2 Sewer lines
5 Cess pool
8 Sewage lagoon
11 Fuel storage
15 Oil well/ Gas well
3 Watertight sewer lines
6 Seepage pit
9 Feedyard
12 Fertilizer storage
16 Other (specify below)
13 Insecticide storage

Direction from well?
How many feet?

FROM
TO
CODE
LITHOLOGIC LOG
FROM
TO
PLUGGING INTERVALS

0
17
CL-ML
Silty Clay, mod to high plasticity, granular

17
25
ML
Silt, low plasticity, with clay

25
37
CL
Clay

37
43
SP
Sand, very fine to fine grain, subangular to subrounded, quartz

7
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was
(1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr)
9-16-05

Water Well Contractor's License No.
531

under the business name of
Geotechnical Services, Inc.

This Water Well Record was completed on (mo/day/yr)
10-11-05

by (signature)

INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.