

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Saline		NW ¼	NE ¼	NW ¼	26	T 14 S		R 3 E/W	

Distance and direction from nearest town or city street address of well if located within city?
1121 W. Cloud, Salina

2	WATER WELL OWNER:	Kwik Shop, Inc.	
	RR#, St. Address, Box #	: P.O. Box 1927	
		: Hutchinson, Kansas 67504-1927	Board of Agriculture, Division of Water Resources
	City, State, ZIP Code	:	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

W E

N S

SW SE NW NE

X

4 DEPTH OF COMPLETED WELL 42 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr

Pump test data: Well water was NA ft. after hours pumping gpm

Est. Yield NA gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8 in. to 42 ft. and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring

9 Dewatering

12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No ☒ ; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No ☒

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued	Clamped
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded	
		7 Fiberglass		Threaded	✓

Blank casing diameter 2 in. to 27 ft. Dia in. to ft. Dia in. to ft.

Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL

1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 27 ft. to 42 ft. From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 25 ft. to 42 ft. From ft. to ft. From ft. to ft.

6] GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other Concrete
Grout Intervals:		From 0 ft. to 1 ft.	From 1 ft. to 2 ft.	From 2 ft. to 3 ft.	From 3 ft. to 4 ft.
What is the nearest source of possible contamination:				10 Livestock pens	14 Abandoned water well
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage		
Direction from well?				How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Concrete,			
0.5	15	Sand (m-f), loose, damp (fill), Reddish Brown			
15	20	Clay, tr. silt, soft, med. plas., damp, Dark Bro			
20	21	Silt, tr. clay, v. soft, damp, mild odor, Olive Br			
21	21.5	Clay, v. soft, high plasticity, damp, Med. Brow			
21.5	25	Clay, some silt, soft, low plas., damp, Olive Br			
25	26	Clay, silty, v. soft, low plas., damp, Med. Brow			
26	30	Clay, w/silt, v. soft, tr. plas., mild petrol odor,			
30	35	Sand (m-f), poorly graded, moist at 31', loose,			
35	42	Sand (f-c), tr. gravel to 1", wet @ 35', Med. to			
					MW1 , Flushmount
					Project Name: Trileaf - Kwik Shop, West Cloud, Salina
					GeoCore # 1319 , #

7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/14/2006 and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 9/15/06
under the business name of GeoCore, Inc. by (signature) Don Bell