

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Saline</u>		<u>SW 1/4 NE 1/4 SW 1/4</u>	<u>36</u>	<u>T 14 S</u>	<u>R 3 E</u>
Distance and direction from nearest town or city street address of well if located within city? <u>319 Gail</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :		<u>Salina, KS 67401</u>			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>59</u> ft. ELEVATION: <u>1241</u>			
		Depth(s) Groundwater Encountered 1. <u>28</u> ft. 2. <u>28</u> ft. 3. <u>28</u> ft.			
		WELL'S STATIC WATER LEVEL <u>28</u> ft. below land surface measured on mo/day/yr <u>5-5-07</u>			
		Pump test data: Well water was <u>28</u> ft. after <u>1 1/2</u> hours pumping <u>15</u> gpm			
		Est. Yield <u>30</u> gpm: Well water was <u>28</u> ft. after <u>1 1/2</u> hours pumping <u>15</u> gpm			
		Bore Hole Diameter <u>30</u> in. to <u>30</u> ft., and <u>30</u> in. to <u>30</u> ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>X</u> No <u>X</u>			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <u>X</u> Clamped <u>X</u>			
1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass 10 Asbestos-cement			
Blank casing diameter <u>4</u> in. to <u>39</u> ft., Dia. <u>4</u> in. to <u>39</u> ft.		Casing height above land surface <u>14</u> in., weight <u>50</u> lbs./ft. Wall thickness or gauge No. <u>SDR26</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From <u>39</u> ft. to <u>59</u> ft., From <u>39</u> ft. to <u>59</u> ft. From <u>39</u> ft. to <u>59</u> ft., From <u>39</u> ft. to <u>59</u> ft.			
GRAVEL PACK INTERVALS:		From <u>25</u> ft. to <u>59</u> ft., From <u>25</u> ft. to <u>59</u> ft. From <u>25</u> ft. to <u>59</u> ft., From <u>25</u> ft. to <u>59</u> ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout intervals: From <u>0</u> ft. to <u>25</u> ft., From <u>0</u> ft. to <u>25</u> ft., From <u>0</u> ft. to <u>25</u> ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage 17 Other (specify below)			
1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard		How many feet? <u>15</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	53	6" Plastic well casing			This well was originally 53' to the best of my knowledge & was reconstructed with a 4" well casing to 59' deep
0	59	4" SDR26 well casing			
		gravel packed between casings to 25' and neat cement grouted to top			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5-5-07</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>523</u> This Water Well Record was completed on (mo/day/yr) <u>5-5-07</u> under the business name of <u>M+D Well Service</u> by (signature) <u>Matthew Janke</u>					