			WATER	R WELL RECORE	Form W	WC-5	KSA 8	32a-121	12 ID N	ło				
	ON OF WATER		Fraction				on Nun	nber	Town	ship Nur	nber	Ran	ge Numb	er
County:		ine	SW ¼	NW ¼	SW ½		12		Т	14	S	R	3	w
Distance and 353 N 7 <sup>th</sup>	d direction from St., Salina	n nearest tow	n or city street add	ress of well if loo	cated within	city?								
		. Union	Pacific Railro	ad Compar	1V						<del></del>			
_			ouglas St., M	•	•				Board	of Agricu	Itura Div	ision of W	latar Dan	01/2000
			a, Nebraska (							ation Nun		151011 01 44	alei Nes	ources
LOCATE	WELL'S LOC	ATON WITH												
AN X IN	SECTION BO	OX:	DEPTH OF C	OMPLETED WE	LL	60	ft.	ELEVA	ATION:			·		ے ا
T I			Depth(s) Groundv											
	NW	NE	WELL'S STATIC											}
₩ W L	i	_	Pump	test data: Wei	li water was	·		ft.	after		hours	oumping		gpm c
₹ W		-	Est. Yield	gpm: Wel	ll water was	•		ft.	after		hours I	oumping		
l x	sw	SE	Bore Hole Diamet			00	nnly	f	t. and	nondition	ina 1	n. to		ft.
	i	1		3 Feed lot	6 Oil fie	id water su	upply		9 Dev	vatering	'''y 1	2 Other	Specify I	below)
† <u>L</u>		i.	2 Irrigation	4 Industrial										
	S		Was a chemical/b											e was
			submitted	and and and and and	pio oubii		орини					, moracy,		
5 TYPE OF	F BLANK CAS	ING USED:		5 Wrought Iro	on 8	Concre	te tile					ed		ed
1 Ste		3 RMP (	(SR)	6 Asbestos-C							Wel			
2 PV	C -	4 ABS	· •	7 Fiberglass		•	,		•			ded	Flus	sh
			in. to 55			in to	· · · · · · ·		ft Dia					
Casing heig	ht above land	surface F	lushmount	in weight	0.7	03	 th	s/ft \	Vall thick	ness or o	auge No		SCH. 4	io "
			N MATERIAL:	,g					7					
1 Ste		3 Stainle		5 Fiberglass										
2 Bra			nized steel	6 Concrete ti	le	9 ,	ABS Ì	•	1	2 None	used (op	en hole)		
SCREEN O	R PERFORAT			5					8 Saw	cut		11 Nor	ne (open	hole)
	ntinuous slot		Mill slot		Wire wrap				9 Drille					
	vered shutter		Key punched		Torch cut				10 Othe	er (specif	fy)			
SCREEN-PI	ERFORATED	INTERVALS		<b>55</b> ft. to				_						
00	AVEL DAGK (A	ITED (ALC		ft. to										
GRA	AVEL PACK II	NIERVALS:	_	.53 ft. to										ft.
6 00015		4	From		)			ft. Fr		Dante		to		ft.
O GROUT	MATERIAL:	1 Neat	cement 2	Cement grout	E4	3 Bent	tonite		4 Other	Bento	onite G	rout		
Grout Interv	als From		ft. to 51	ft. From	51	ft. t	٠	2	ft.	From		ft. to		ft.
	nearest source ptic tank	e or possible	contamination:	7 F	lik maka .				ock pens			bandoned		ell
	wer lines		4 Lateral lines 5 Cess pool		ewage lag	oon			torage zer storag			il well/ Ga ther (spe		w
	itertight sewer	lines	6 Seepage pit		eedyard	0011			icide stor		.0 0	alei (spe	ony belov	•,
Direction fro	-		o coopage pa	•	oodyara			many		ugo				
FROM	то	CODE		OGIC LOG		FROM	Т			PLU	JGGING	INTERVA	LS	
00	2.5		oncrete											
2.5 7.5	7.5 15	Si	It and Clay, b	rown										
15	17.5		ayey Silt, browlet and Clay, b				-	-+						
17.5	27.5		Ity Clay, brow				+	$\rightarrow$						
27.5	30		ayey Sand, b											
30	32.5	Sa	andy Clay, bro	own										
32.5	60	Sa	and, fine to coa	rse grained										
							-							
							-							
		<del></del>					-							
		<del></del>					+							
7 CONTR	ACTOR'S OR	LANDOWNE	R'S CERTIFICAT	ION: This water	well was (	1) constru	cted (	2) reco	nstructed	, or (3) pi	ugged un	der my ju	risdiction	and was
	on (mo/day/yr)		07/1		<u></u>							edge and		
	Contractor's L			531								no/day/yr)		27/07
	usiness name		Geotechnic		inc.			ature)	1/ /	lin		31 31 )		
INSTR	RUCTIONS: PIE	ease fill in blan	ks and circle the cor	rect answers. Ser	nd three cop	ies to Kans	sas De	partmer	nt of Healt	h and Env	ironment,	Bureau of	Water, 10	000 \$ W
Jackso	on St., Ste. 420,	ropeka, Kans	as 66612-1367. Tel	ephone: 913-296	-5545. Sen	d one to W	ATER	WELL (	OWNER a	nd retain	one for yo	ur records		