				ATER WELL RECO	ORD Form			2a-1212		
	ION OF WATE		l <u>-</u>	CVA	0144		tion Num			Range Number
County:		line		y ₄ SW y ₄ t address of well if	SW located wit	/ -	12	т 14	S	R 3 W
Distance at	na anechon no	iii iieaiest to	wir of city stree	301 W. As		,	(ansas			
2 WATER	WELL OWNE	R: Bill R	eimold							
	ddress, Box#							Board of Agricu	ture Div	rision of Water Resources
City, State.	ZIP Code	Salin	a, KS 6740	2				Application Nun		Total of Trailor Hoodardoo
LOCATI	E WELL'S LOC	ATON WITH	1 4			20				
AN "X" I	IN SECTION B	OX:	DEPTH C	OF COMPLETED V	VELL	39	ft. E	LEVATION:		3 Ft. 9
	N		I					nd surface measured or		/yr 05/15/08
1 1 I	i I									pumping Gpm
	n'w	NE	Est. Yield	Gpm: V	Vell water v	vas		Ft. after	Hours	pumping Gpm
0	i I	i]	Bore Hole Dia	R TO BE USED A	_In. to .S∵ 5 Pui	Jic water si	innly	ft. and	ii 1	n. to Ft. 1 1 Injection well 2 Other (Specify below)
<u>₹</u> W -			1 Dome	estic 3 Feed lot	6 Oil	field water s	supply	9 Dewatering	1	2 Other (Specify below)
			2 Irrigat	tion 4 Industria	1 7 Lav	vn and gard	len (dom	estic) 10 Monitoring v	vell	MW-10
	SW	SE	Was a chemi							, mo/day/yr sample was
↓ ×	(Submitted	our suctoriological	ap.o oa	2		Water Well Disinfected		
5 TYPE O	F BLANK CAS	ING USED:		5 Wrought	Iron	8 Concre				d Clamped
1 St			(SR)	9					Weld	
2 PV		T 4 ABS	, ,	7 Fiberglas						aded X
_		_		Ft				· · · · · · · · · · · · · · · · ·	ine	aueu
Blank casin	ng diameter	2	in. to	19 Dia		In. t	0	ft., Dia		in. to ft.
Casing heig	ght above land	surface	FLUSH	In., weight	SC	H 40	Lbs	s./ft. Wall thickness or g	auge No).
			ON MATERIAL:			7	PVC	10 Asbes	tos-ceme	ent
1 Ste	eel	3 Stain	less steel	5 Fiberglas	SS		RMP (SF	R) 11 Other	(specify)	
2 Bra			anized steel			9	ABS	12 None	used (op	en hole)
	OR PERFORAT					wrapped				11 None (open hole)
	ontinuous slot		Mill slot		6 Wire w			9 Drilled holes		
	uvered shutter		Key punched		7 Torch o		,	10 Other (specify	/)	
SCREEN-F	PERFORATED	INTERVAL								toft.
	ND DAOK INT	-DV441-0		π.	10	20	¹	π. From	π. ·	to Ft.
SA	ND PACK INT	ERVALS:	From		to		I	π. From	π.	to Ft.
6 6 6 6 6 6 6		4 11	From	ft.				ft. From		to Ft.
GROUT	MATERIAL:	1 Near	cement	2 Cement grout Ft.		3 Ben	tonite	4 Other		
Grout Inten	vals From3	0	ft. to 1	5 From2	15	to		17 ft. From		ft. to ft.
			contamination:					vestock pens		andoned water well
1 Se	eptic tank		4 Lateral lin	es 7	Pit privy		11 Ft	uel storage	15 Oil	well/ Gas well
2 Se	wer lines		5 Cess poo	I 8	Sewage la	agoon	12 Fe	ertilizer storage	16 Ot	her (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Contaminated Site										
Direction fro	om well?							any feet?		
FROM	ТО	CODE	LITH	HOLOGIC LOG		FROM	ТО	PLUC	GING II	NTERVALS
0	.5		oncrete							
.5	20			ry dark browi	n, low					
20	30	C	layey Silt, t	prown, soft	oint he		-			
30 39	39 TD		nd of Borel	race sand, m	ioist,br		-			
33	10		na or borer	IOIE						
							1			
7 CONTR	ACTOR'S OP		R'S CERTIFIC	ATION: This water	ar well was	(x) construc	ted (2) -	reconstructed of (2) =1::	0004	der my jurisdiction and w
Completed	on (moldaulur)	LANDOVVINI	05	5/15/08	well Was					
				585				is true to the best of my		
dar tha h	Contractor's Li	-6	Accor	isted Environ	nmontal	Inc		Record was completed	41018	120
INSTR	usiness name	or ase fill in blan	ks and circle the	correct answers Se	and three co	pies to Kans	as Denado	By (signature) Bra ment of Health and the	ulcyst)	JUMISON Water Tondo
Kansa	s 66620-0001	Telephone: 9	13-296-5545 Se	nd one to WATER V	NELL OWN	FR and retain	one for v	Our records		прока,