

1) LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number		
County: Saline		NE ¼ SE ¼ SW ¼	1	T 14 S	R 3 E W		
Distance and direction from nearest town or city street address of well if located within city? 1014 N. Third, Salina							
2) WATER WELL OWNER: Kansas Dept. of Transportation RR#, St. Address, Box # : 1014 N. Third City, State, ZIP Code : Salina, Kansas 67401 Board of Agriculture, Division of Water Resources Application Number:							
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4) DEPTH OF COMPLETED WELL 35 ft. ELEVATION: 1218.63 Depth(s) Groundwater Encountered 1..... ft. 2..... ft. 3..... ft. WELL'S STATIC WATER LEVEL ... 24.65 ... ft. below land surface measured on mo/day/yr ... 6/26/2008 ... Pump test data: Well water was NA .. ft. after hours pumping gpm Est. Yield .. NA .. gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 35 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No✓ ; If yes, mo/day/yr sample was submitted Water Well Disinfectad? Yes No ✓					
5) TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 20 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface -4.56 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 20 ft. to 35 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 18 ft. to 35 ft., From ft. to ft. From ft. to ft., From ft. to ft.							
6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete Grout Intervals: From 0 ft. to 1 ft., From 1 ft. to 10 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? How many feet?							
FROM		TO		LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0		0.5		Asphalt,			
0.5		5		Clay, silty, moist, no odor, Brown to Dark Bro			
5		11		Clay, v. silty, v. moist, no odor, Lt. Brown			
11		14		Clay, silty, moist, Gray-Brown			
14		19		Clay, v. silty, v. moist, soft, Gray			
19		26		Clay, sl. silty, moist, stiff., Gray			
26		30		Clay, sl. silty, saturated, Gray			
30		35		Silt w/occ. sand stringers (f-c), Gray			
							MW4/SB4 , Tag # 0042889 , Flushmount
							Project Name: KDOT - Salina (LSA)
							GeoCore # 1448 , KDHE # U5 085 00268
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/12/2008 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 7/2/2008 under the business name of GeoCore, Inc. by (signature) Dale Hall							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-298-5545. Send one to WATER WELL OWNER and retain one for your records.							