

1 LOCATION OF WATER WELL: County: SALINE	Fraction SW 1/4 NW 1/4 NW 1/4	Section Number 24	Township Number T 14 S	Range Number R 3 E
Distance and direction from nearest town or city street address of well if located within city? 821 Highland				
2 WATER WELL OWNER: RR#, St. Address, Box # : 821 Highland City, State, ZIP Code : SALINA, KS 67401				
Board of Agriculture, Division of Water Resources Application Number: 57 67401				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 57 ft. ELEVATION: 1228		
		Depth(s) Groundwater Encountered 1 34 ft. 2 34 ft. 3 5-15-89 ft. WELL'S STATIC WATER LEVEL 34 ft. below land surface measured on mo/day/yr 5-15-89 Pump test data: Well water was 36 ft. after 3/4 hours pumping 189 gpm Est. Yield 30 gpm: Well water was 36 ft. after 3/4 hours pumping 189 gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) ① Domestic (lawn & garden) 10 Monitoring well		
		Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted 5-16-89		
		Water Well Disinfected? Yes X No X		
5 TYPE OF BLANK CASING USED:				
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped ② PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded				
Blank casing diameter 5 in. to 47 ft. Dia 160 LB in. to 57 ft. Dia 57 in. to 57 ft.				
Casing height above land surface 17 in. weight 160 LB lbs./ft. Wall thickness or gauge No. SDR26				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify) 9 ABS 12 None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:				
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) 45 FT				
SCREEN-PERFORATED INTERVALS: From 47 ft. to 57 ft. From 47 ft. to 57 ft. From 47 ft. to 57 ft.				
GRAVEL PACK INTERVALS: From 22 ft. to 33 ft. From 3.5 ft. to 57 ft. From 3.5 ft. to 57 ft.				
6 GROUT MATERIAL: ① Neat cement 2 Cement grout ③ Bentonite 4 Other				
Grout Intervals: From 0 ft. to 22 ft. From 33 ft. to 35 ft. From 35 ft. to 57 ft.				
What is the nearest source of possible contamination:				
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well ③ Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? West How many feet? 45 FT				
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS		
0'	3'	Fill dirt		Neat cement plug
3'	5'	Dark top soil		From 33' to 35'
5'	16'	Brown clay		
16'	20'	Fine sand		And Bentonite from
20'	35'	Brown clay		22' to ground level
35'	40'	Medium sand & Br. Clay		
40'	41'	Grey clay		
41'	56'	Medium & coarse sand & gravel		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-16-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 523 This Water Well Record was completed on (mo/day/yr) 5-16-89 under the business name of M+D Well Service by (signature) Matthew Soukup				