

1 LOCATION OF WATER WELL: County: SALINE	Fraction SW 1/4 NE 1/4 NE 1/4	Section Number 25	Township Number 14 E	Range Number 3 EW
Distance and direction from nearest town or city street address of well if located within city? 504 Kensington				
2 WATER WELL OWNER: Dan + Alice Sauber				
RR#, St. Address, Box # : 504 KENSINGTON		Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Salina, KANSAS 67401		Application Number: 1232		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 46 ft. ELEVATION: 1232 ft.		
		Depth(s) Groundwater Encountered 19 ft. 2 19 ft. 3 19 ft.		
		WELL'S STATIC WATER LEVEL 19 ft. below land surface measured on mo/day/yr 5-30-09		
		Pump test data: Well water was 19 ft. after 1 hours pumping 15 gpm		
		Est. Yield 25 gpm: Well water was 19 ft. after 1 hours pumping 15 gpm		
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No				
5 TYPE OF BLANK CASING USED:				
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued X Clamped
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)		Welded
Blank casing diameter 5 in. to 36 ft. Dia		Threaded		
Casing height above land surface 17 in., weight 160 lbs./ft. Wall thickness or gauge No. 7DR 26				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR)		10 Asbestos-Cement		
2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS		11 Other (Specify)		
		12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:				
1 Continuous slot 3 Mill slot		5 Gauzed wrapped 8 Saw cut		11 None (open hole)
2 Louvered shutter 4 Key punched		6 Wire wrapped 9 Drilled holes		
		7 Torch cut 10 Other (specify)		
SCREEN-PERFORATED INTERVALS: From 36 ft. to 46 ft., From 43 ft. to 46 ft.				
GRAVEL PACK INTERVALS: From 22 ft. to 39 ft., From 43 ft. to 46 ft.				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other				
Grout Intervals: From 0 ft. to 22 ft., From 43 ft. to 46 ft.				
What is the nearest source of possible contamination:				
1 Septic tank 4 Lateral lines 7 Pit privy		10 Livestock pens 14 Abandoned water well		
2 Sewer lines 5 Cess pool 8 Sewage lagoon		11 Fuel storage 15 Oil well/Gas well		
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		12 Fertilizer storage 16 Other (specify below)		
Direction from well? South & West		How many feet? 18' And 18'		
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS		
0'	3'	Kill dirt & topsoil		
3'	22'	Brown clay		
22'	27'	Brown clay and sand mixed		
27'	39'	Medium sand		
39'	43'	Brown clay		
43'	46'	Coarse sand & gravel		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-30-09 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 523 This Water Well Record was completed on (mo/day/yr) 5-30-09 under the business name of M&D well Service by (signature) Matthew Soukup				
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.				