WATE	R WEI	LL RECORD	Form WV	VC-5	Division of Wate	r Resources App. N	0.	
		OF WATER WELL:	Fraction		Section Number	Township No.	Range Number	
	ıty: Sali		NE 1/4 SE 1/4 NE		11	T 14 S	R 3 □E <b>☑</b> W	
	Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here							
	T ===================================							
	349 N 9th Street					Elevation: 1225.08 ft		
Salina, Kansas					<u>Datum</u> : ☐ WGS 84, <b>☑</b> NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: KDHE/BER SWP-3					Collection Method:  ☐ GPS unit (Make/Model: Thales/MobileMapp)			
RR#, Street Address, Box #: 1000 SW Jackson Suite 410 City, State, ZIP Code : Topeka KS 66612					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
City, State, ZIP Code : Topeka, KS, 66612					Est. Accuracy:			
3 LOCATE WELL								
	TTH AN "X" IN Depth(s) Groundwater Encountered (1),25,79 ft. (2) ft. (3) ft.							
SEC	N N	7 2 20						
	Pump test data: Well water wasft. after hours pumping							
l l	EST. YIELDgpm. Well water wasft. after hours pumpinggpm							
w   N	W Bore Hole Diameter 8							
<del> </del> +	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☑ Monitoring well								
s If yes, mo/day/yr sample was submitted 6/17/09								
mile  Water well disinfected?								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS:  Glued  Clamped  Welded  Threaded								
Casing diameter .2 in. to .30 ft., Diameter in. to ft., Diameter ft.								
Casing height above land surface. 0								
TYPE OF SCREEN OR PERFORATION MATERIAL:         □ Steel       □ Other (Specify)								
☐ Steel       ☐ Stainless Steel       ☐ PVC       ☐ Other (Specify)         ☐ Brass       ☐ Galvanized Steel       ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot  Mill slot  Gauze wrapped  Torch cut  Drilled holes  None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)  SCREEN-PERFORATED INTERVALS: From 30								
From								
GRAVEL PACK INTERVALS: From 28								
From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From .0.5 ft. to .28 ft., From ft. to ft. ft. to								
What is the nearest source of possible contamination:   Septic tank								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well								
Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well 1-1DCE Plume								
FROM	TO TO	n well .NW	TIC L OC	FROM			JGGING INTERVALS	
0	8	Silty Clay	iic Log	FROM	TO LITHO. L	od (cont.) or PLC	OGGING INTERVALS	
8	13	Silt						
13	17	Silty Clay						
17	22	Silt						
22	26	Sand						
26	36	Clayey Silt				···		
36	40	Sand						
40	42	Clayey Silt	171.0.					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was  ✓ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .6/15/09 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. Exempt This Water Well Record was completed on (mo/day/year). 7/22/09								
under the business name of KDHE/BER by (signature) Grat. Urita								
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								