WATER WELL RECORD	Form WV	VC-5		er Resources App. No	· · · · · · · · · · · · · · · · · · ·	
1 LOCATION OF WATER WELL: County: SALVE	Fraction NW1/4 NW1/4 SE	.1/2 ST 1/2	Section Number	Township No. T / S	Range Number	
Street/Rural Address of Well Location;			Global Positioning		the state of the s	
from nearest town or intersection: If at owner's address, check here		Global Positioning System (GPS) information: Latitude:				
		Longitude: (in decimal degrees)				
831 JOANIE LANE			Elevation:			
2 WATER WELL OWNER: DACE	ICK HOSHA	i)	Datum: WGS 84, NAD 85, NAD 27 Collection Method:			
2 WATER WELL OWNER: DACEICE HOSHAW RR#, Street Address, Box #: \$31 JOA 101E LANK			GPS unit (Make/Model:) Digital Map/Photo, Topographic Map, Land Survey			
City, State, ZIP Code : SAL	INA TO 6	27401	☐ Digital Map/Pl Est. Accuracy: ☐ <	noto, ∐ Topographio <3 m. □ 3-5 m. □	c Map, ∐ Land Survey 5-15 m. □ >15 m	
A TOOLOW YUNT Y						
WITH AN "X" IN 4 DEPTH OF	COMPLETED WELL		ft.	0 (2)	
SECTION BOX: Depth(s) Groun	Depth(s) Groundwater Encountered (1)ft. (2)ft. (3)ft. WELL'S STATIC WATER LEVEL. 3ft. below land surface measured on mo/day/yr 23					
Pumi	Pump test data: Well water wasft. after hours pumping					
NW NE EST. YIELD	EST. YIELDgpm, Well water was ft. after hours pumping gpm					
W E Bore Hole Dian	E Bore Hole Diameter					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below)						
SW SE						
Was a chemical/bacteriological sample submitted to Department? Yes X No						
S If yes, mo/day/yr sample was submitted						
Water well disinfected? Yes No						
5 TYPE OF CASING USED: Steel PVC Other						
CASING JOINTS: Glued Clamped Welded Threaded						
Casing diameter						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
☐ Steel ☐ Stainless Steel ☐ Other (Specify)						
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot X Mill slot - Description Gauze wrapped Torch cut Drilled holes None (onen hole)						
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft.						
SCREEN-PERFORATED INTERVALS: From						
GRAVEL PACK INTERVALS: From 22 ft. to 55 ft., From ft. to ft.						
From ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other						
Grout Intervals: From						
Septic tank						
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well						
Watertight sewer lines Seepage Direction from well Soul. T.t.			from well			
FROM TO LITHOLO	O M A LA MANAGEMENT AND A CONTROL OF THE CONTROL OF	FROM			JGGING INTERVALS	
03, FILL DIET						
	O SIRTY				Walter 1997	
18 32 SANDY LOOP	N TAND					
32 55 SAND FINE CLAY GLAX	TO MED TAN	'				
Chily GFAF	LA RAINBIALDONNESS CONTRACTOR CON					
					was a second and a second a second and a second a second and a second a second and a second and a second a second a second	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was **Constructed. reconstructed. or plugged						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, rec						
Kansas Water Well Contractor's License No. 301 This Water Well Record was completed on (mo/day/year) under the business name of HESTINGER PHM SEL by (signature)						
under the business name of .T. L. J. J. J. L. L. by (signature) by (signature) INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies						
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.						
Telephone 785-296-5522. Send one copy to WA	TER WELL OWNER and	retain one for	our records. Include f	ee of \$5.00 for each	constructed well. Visit us at	
http://www.kdheks.gov/waterwell/index.html.	KSA 82a-1212					