WATER WELL RECORD			Form W	WC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL:			Fraction		Section Number Township No. Range Number
County: Saline			¼ Near¼ Ctr	: 1/4 SE 1/2	$4 \mid 36 \mid T \mid 14 \mid S \mid R \mid 3 \mid E \mid 2 \mid 2 \mid W \mid$
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:					
from nearest town or intersection: If at owner's address, check here . Latitude:					
in S	alina	City Limits, 2872	Melanie Lane		Longitude: (in decimal degrees)
		- ,			Elevation:
2 WAT	FD WE	LL OWNER: Kelly	D 0 1 1	•	<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27
1		11 2 "	Dunn Construct		Collection Method:
1 C' C' 7TD C 1			Quail Creek Rd.	1	☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey
City,	State, Z	Salin	a, KS 67401		Est. Accuracy: \square <3 m, \square 3-5 m, \square 5-15 m, \square >15 m
3 LOCATE WELL					
i	AN "X"	IN 4 DEPTH OF C			ft.
SECTI	ION BOX	X: Depth(s) Ground	water Encountered	(1)	ft. (2) ft. (3) ft.
	WELL'S STATIC WATER LEVEL26ft. below land surface measured on mo/day/yr. 8/8/1.2				
		Pump	test data: Well wate	r was	ft. after hours pumping gpm
NW	NE				ft. after hours pumping gpm
W E Bore Hole Diameter 9in. to5.4ft., andin. toft.					
SW SE ₋₂					
☐ Irrigation ☐ Industrial ☑ Domestic-lawn & garden ☐ Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes X No					
S If yes, mo/day/yr sample was submitted					
Water well disinfected? ▼ Yes No					
5 TYPE OF CASING USED: Steel X PVC Other					
CASING JOINTS: X Glued Clamped Welded Threaded					
Casing diameter					
Casing height above land surface					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
☐ Steel ☐ Stainless Steel ☐ Other (Specify)					
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)					
Continuous stot					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From					
From					
GRAVEL PACK INTERVALS: From					
From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: Neat cement Cement grout XX Bentonite Other					
Grout Intervals: From					
What is the nearest source of possible contamination:					
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)					
Sewer lines					
X Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Direction from well ☐ Distance from well ☐ 1.00.¹					
					e from well100.
FROM	TO	LITHOLOG	IC LUG	FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0		Topsoil			
5		Clay, brown			
22	30	Clay, silty tan			
30	,	Sand, fine to med			
41		Sand, fine to coar			
56	60	Sand and Gravel, 1	red		
-					
				-	
	D 4 677 1	DIG OD I LYD OWNER	10 OEDWING : TO	NI CDI:	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was \(\subseteq \) constructed, \(\subseteq \) reconstructed, or \(\subseteq \) plugged					
under my jurisdiction and was completed on (mo/day/year) .8/8/12 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No					
under the business name of Peterson. Irrigation, Inc by (signature) by (signature) INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies					
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.					
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at					
http://www.kdheks.gov/waterwell/index.html.					
KSA 82a-1212					