WATER WELL RECORD Form WWC-5	Division of Water Resources; App. No.
1 LOCATION OF WATER WELL: Fraction County: Salina SW 1/2 SE 1/2 NW	Section Number Township Number Range Number T 14 S R 3 W
Distance and direction from nearest town or city street address of well	Il if Global Positioning System (decimal degrees, min. of 4 digits)
located within city?	Latitude: 38.85050° Longitude: 97.62576°
1372 West North Street, Salina 2 WATER WELL OWNER: Mid Kansas Cooperative	Elevation: TOC: 1220.31; RIM: 1219.96
RR#, St. Address, Box # : 307 W Cole, P.O Box D	Datum: NAD29
City, State, ZIP Code : Moundridge, KS 67107	
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 2	
LOCATON	MW12
WITH AN "X" IN Depth(s) Groundwater Encountered 1	ft. 2 ft. 3 ft
SECTION BOX: WELL'S STATIC WATER LEVEL 19.	ft. 2 ft. 3 ft. 48 ft. below land surface measured on mo/day/yr 3/21/12*
N Pump test data: Well water was	ft after hours pumping gram
Fst Vield onm: Well water was	ft. after hours pumping gpm ft. after hours pumping gpm
WELL WATER TO BE USED AS: 5 Pub	plic water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feed lot 6 Oil field water	er supply 9 Dewatering 12 Other (Specify below)
W E 2 Irrigation 4 Industrial 7 Domestic (lay	wn & garden) (O)Monitoring well
SW SE	vii de gai don)
Was a chemical/bacteriological sample sub	omitted to Department? Yes No X; If yes, mo/day/yrs
	Water Well Disinfected? Yes No X
F TYPE OF CLOPIC VICES 5 W. 1.1.	CASDIC IONTES Chad Charact
5 TYPE OF CASING USED: 5 Wrought Iron 8 C	oncrete tile CASING JOINTS: Glied Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 C	Other (specify below) Welded
2 PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 10.3 ft., Dia	Threaded X
Blank casing diameter 2 in. to 10.3 ft., Dia	in. to t., Dia in. to t.
Casing height below land surface 0.35 ft., Weight	lbs./ft. Wall thickness or gauge No.
1 Steel 2 Stainless steel 5 Fibersless (7) BVC	0 ADC 11 Other (marify)
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR)	10 A shestos Cement 12 None used (open hole)
DOUBLE IN OR FERROIR A CHOIN OPENINGS ARE:	· · · · · · · · · · · · · · · · · · ·
1 Continuous slot 2 Mill slot 5 Gauze wrapped 7 2 Louvered shutter 4 Key punched 6 Wire wrapped 8	Torch cut 9 Drilled holes 11 None (open hole)
2 Louvered shutter *Key punched 6 Wire wrapped 8	Saw Cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 10.3 ft.	to 25.3 ft. From ft. to ft.
From II.	to II. From II. to II.
GRAVEL PACK INTERVALS: From 8 ft.	to 25.6 ft. From ft. to ft.
From ft.	to ft. From ft. to ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout (3	Bentonite (4)Other Concrete: 0-1ft
Grout Intervals From 1 ft. to 8 ft. From	ft. to ft. From ft. to ft.
What is the nearest source of possible contamination:	
	ivestock pens 13 Insecticide Storage 16 Other (specify
2 Sewer lines 5 Cess pool 8 Sewage lagoon (11) F	
	ertilizer storage 15 Oil well/ gas well
Direction from well? SW How	many feet? ~280ft
FROM TO LITHOLOGIC LOG F	ROM TO PLUGGING INTERVALS
0 25.6 Brown soft silty clay	
	Flushmount waiver from BOW
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged	
under my jurisdiction and was completed on (mo/day/year) 10/3/12 and this record is true to the best of my knowledge and belief.	
Kansas Water Well Contractor's License No. 757 This Water Well Record was completed or (medday/year) 10/5/12	