WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL: County: Saline	Fraction 1/4 SW 1/4 SW 1/4 SW	Section Number Township No. Range Number
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:		
		Latitude: .38,856229 (in decimal degrees) Longitude: 97.665238 (in decimal degrees)
Bunge Salina Elevator 1112 North Halstead Rd., Salina, KS 67401		Elevation: 1242.95
A WILL FIRST WINDY & OWN TOWN		— <u>Datum</u> : ☐ WGS 84, [] NAD 83, ☐ NAD 27
2 WATER WELL OWNER: Bunge North America, Inc. RR#, Street Address, Box #: PO Box 28500		Collection Method: GPS unit (Make/Model:)
City City Film City	s, MO 63146	☐ Digital Map/Photo, ☐ Topographic Map, ☑ Land Survey
Est. Accuracy:		
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 29.5 ft.		
WITH AN "X" IN SECTION BOX: N Depth(s) Groundwater Encountered (1)		
WELL'S STATIC WATER LEVEL 1910 of the below land surface measured on mo/day/yr. Pump test data: Well water was N/A ft. after N/A hours pumping. N/A gpm		
1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -		
W E Bore Hole Diameter 8.25		
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well		
SWSE ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below) ☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☑ Monitoring well P.Z:12		
Was a chemical/bacteriological sample submitted to Department? Yes V No		
S If yes, mo/day/yr sample was submitted. M.A		
. Water well disintected? [] 1 es [[] 100		
5 TYPE OF CASING USED: Steel PVC Other		
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter .1 in. to .29.5 ft., Diameter .N/A in. to .N/A ft., Diameter .N/A ft.		
Casing height above land surface. 30 in., Weight N/A lbs./ft., Wall thickness or gauge No. Schedule 40		
TYPE OF SCREEN OR PERFORATION MATERIAL:		
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)		
SCREEN OR PERFORATION OPENINGS ARE:		
Continuous slot		
SCREEN-PERFORATED INTERVALS: From 19.5 ft to 29.5 ft. From N/A ft to N/A ft.		
From N/A ft to N/A ft From N/A ft to N/A ft.		
GRAVEL PACK INTERVALS: From . 16.5 ft. to . 29.5 ft., From . N/A ft. to . N/A ft. From . N/A ft. to . N/A ft.		
6 CROUT MATERIAL: Neat cement Cement grout V Bentonite V Other 0-2 feet concrete		
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other 0-2 feet concrete Grout Intervals: From .2		
What is the nearest source of possible contamination:		
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below) Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well		
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well		
Direction from well Northwest FROM TO LITHOLOG		te from well < 200-feet TO LITHO. LOG (cont.) or PLUGGING INTERVALS
FROM TO LITHOLOG 0 29.5 well was blind drilled	IC LOG TROM	10 EITHO, EOG (COIL.) OF FEOGGING INTERVALS
you was pina armor		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged		
under my jurisdiction and was completed on (mo/day/year) .12-12-2012 and this record is true to the best of my knowledge and belief.		
Kansas Water Well Contractor's License No759 This Water Well Record was completed on (mo/day/year) .1-18-2013		
under the business name of RAZEK Environmental, LLC by (signature) by (signature) INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies		
(white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at		
http://www.kdheks.gov/waterwell/index.html. KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy		