WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL: County: Saline	Fraction 1/4 SW 1/4 SW 1/4 SW 1/4	Section Number   Township No.   Range Number
Street/Rural Address of Well Location;		Global Positioning System (GPS) information:
		Latitude: .38.856066 (in decimal degrees)
Bunge Salina Elevator		Longitude: 97.661508 (in decimal degrees)
1112 North Halstead Rd., Salina, KS 67401		Elevation: 1237.07 <u>Datum</u> : ☐ WGS 84, ✓ NAD 83, ☐ NAD 27
2 WATER WELL OWNER: Bunge North America, Inc.		Collection Method:
RR#, Street Address, Box #: PO Box 28500		GPS unit (Make/Model:)
City, State, ZIP Code : St. Louis, MO 63146		Digital Map/Photo, Topographic Map, Land Survey
Est. Accuracy:		
WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 33.5 ft. (2) N/A ft. (3) N/A ft.		
SECTION BOX: Depth(s) Ground	Iwater Encountered (1).18.1.15	ft. (2).N/Aft. (3).N/Aft.
WELL'S STATIC WATER LEVEL'S . 15		
Pump test data: Well water was N/A ft. after N/A hours pumping N/A gpm EST. YIELD N/Agpm. Well water was N/A ft. after N/A hours pumping N/A gpm		
W  NW  NE   EST. YIELD 30/24gpm. Well water was 30/24		
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well		
ow gr Domestic Feedlot Oil field water supply Dewatering Other (Specify below)		
Was a chemical/bacteriological sample submitted to Department? Yes V No		
S If yes, mo/day/yr sample was submitted. W.A		
5 TYPE OF CASING USED: Steel PVC Other		
Casing diameter 1. in. to 33.5 ft., Diameter N/A in. to N/A ft., Diameter N/A in. to N/A ft.		
Casing height above land surface. 0 in., Weight N/A lbs./ft., Wall thickness or gauge No. Schedule 40		
TYPE OF SCREEN OR PERFORATION MATERIAL:		
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)		
Brass Galvanized Steel None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:		
Continuous slot  Mill slot  Gauze wrapped  Torch cut  Drilled holes  None (open hole)		
Touvered shutter Key nunched Wire wranged Saw out Other (specify)		
SCREEN-PERFORATED INTERVALS: From 23.5 ft. to 33.5 ft., From N/A ft. to N/A ft. ft.		
GRAVEL PACK INTERVALS: From 20.5 ft. to 33.5 ft., From N/A ft. to N/A ft.		
From N/A ft to N/A ft From N/A ft to N/A ft.		
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other 0-2 feet concrete Grout Intervals: From 2. ft. to 20.5 ft., From N/A ft. to N/A ft., From N/A ft. ft. of the ft. of t		
Grout Intervals: From 2 ft. to 20.5 ft., From N/A ft. to N/A ft., From N/A ft. to N/A ft.		
What is the nearest source of possible contamination:		
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)  Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well		
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well		
Direction from well Northwest	and the same of th	from well _<200-feet
FROM TO LITHOLOG	GIC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0 33.5 well was blind drilled		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ☐ constructed, ☐ reconstructed, or ☐ plugged		
under my jurisdiction and was completed on (mo/day/year) .12-12-2012 and this record is true to the best of my knowledge and belief.		
Wansas Water Well Contractor's License No. 759 This Water Well Record was completed on (mo/day/year) 1-18-2013		
under the business name of RAZEK Environmental, LLC by (signature)		
INSTRUCTIONS: Use ty pewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St. Suite 420, Topeka, Kansas 666 12-1367.		
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at		
http://www.kdheks.gov/waterwell/index.html.  KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy		
KSA 82a-1212		Check: White Copy, Blue Copy, Pink Copy