Cocation of Water Resources App. No.
Distance and direction from nearest town or city street address of well 11 Content within city? 842 N Santa Fe Ave, Salina WATER WELL OWNER: Something Else, LLC RR#, St. Address, Box # P.O. Box 1305 City, State, ZIP Code Salina, KS 67402 LOCATON WITH AN "X" IN SECTION BOX: N Pump test data: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Use a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted 1 Department? Yes No X; If yes, mo/day/yrs Sample was submitted 2 Prof CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted 2 price of the concrete tile CASING JOINTS: Glued Clamped Welcad Threaded X STYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped Welcad Threaded X Slank casing diameter 2 in. to 19.45 ft, Dia in. to ft, Dia in. to ft. Screen No PERFORATION MATERIAL: 1 Neat cement 2 Cement grout 3 Mentonic 4 Other Concrete: 9 Drilled holes 11 None (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 7 From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Mentonic ft. Water well District (4) Other Concrete: 9-Iff. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Mentonic ft. Water well of the concrete: 9-Iff. Grout Intervals From ft. to ft. Water well of the concrete: 9-Iff. Grout Intervals From ft. to ft. From ft. to ft. From ft. to ft. Water well of the concrete: 9-Iff.
WATER WELL OWNER: Something Else, LLC Elevation: NA Datum: NA Data Collection Method: Na Data
WATER WELL OWNER: Something Else, LLC RR#, St. Address, Box # P.O. Box 1305 Datum: NA Datum: N
RR#, St. Address, Box # P.O. Box 1305 City, State, ZIP Code
SIDCATE WELL'S BLOCATON WITH AN "3" IN SECTION BOX: N WELL'S STATIC WATER LEVEL N Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass 3 Blank casing diameter 2 in. to 19.45 ft., Dia in. to ft. Casing height below land surface ft., Weight 1 Steel 3 Stainless steel 5 Fiberglass 1 Steel 3 Stainless steel 5 Fiberglass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 5 CREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 5 Mill slot 5 Gauze wrapped 8 Saw Cut 10 Other (specify) 5 CREEN-PERFORATED INTERVALS: From 19.45 ft. to 34.45 ft. From ft. to ft. 6 GRAVEL PACK INTERVALS: From 18 ft. to 34.86 ft. From ft. to ft. What is the nearest source of possible contamination:
LOCATON WITH AN "X" IN SECTION BOX: N Depth(s) Groundwater Encountered1 WELL'S STATIC WATER LEVEL Pump test data: Well water was Pump test data: Well beaver supply Pup Dewatering Pup Dew
WITH AN "X" IN SECTION BOX: N WELL'S STATIC WATER LEVEL WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted Water Well Disinfected? Yes No X TYPE OF CASING USED: Steel 3 RMP (SR) 6 Asbestos-Cement Other (specify below) Welded Pump test data: Well water was WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE USED AS: 5 Public water supply WELL WATER TO BE Used AS: 5 Public water supply WELL WATER TO BE Used AS: 5 Public water supply WELL WATER TO BE Used AS: 5 Public water supply WELL WATER TO BE Used AS: 5 Public water supply WELL WATER TO BE Used AS: 5 Public water supply WELL WATER TO BE Used AS: 5 Public water supply WELL WATER TO BE Used AS: 5 Public water supply WELL WATER TO BE Used AS: 5 Public water supply WELL WATER TO BE User AS: 5 Public water supply WELL WATER TO BE User AS: 5 Public water supply WELL WATER TO BE User AS: 5 Public wate
Pump test data: Well water was ft. after hours pumping gpm Well Water Was ft. after hours pumping gpm Well Water To Be USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 1 Domesting well 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 1 Domesting well 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 1 Domesting well 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Water Well Disinfected? Yes No X Sample was submitted 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded X Sanghe keight below land surface ft., Weight Issel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 1 Continuous slot 3 Mill slot 5 Gauze wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 19.45 ft. to 34.45 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 19.45 ft. to 34.80 ft. From ft. to ft.
Pump test data: Well water was ft. after nours pumping gpm well well after nours pumping gpm pumping gpm well well after nours pumping gpm pumping defended to Department? Yes No X ; If yes, mo/day/yrs No X ; If yes, mo/da
Est. Yield gpm: Well water was fi. after hours pumping gpm well water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (DMonitoring well was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted Water Well Disinfected? Yes No X Sample was submitted 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X Threaded X Slank casing diameter 2 in. to 19.45 fi., Dia in. to fi., Dia in. to fi. Casing height below land surface fi., Weight Ibs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify) SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot (3) Mill slot 5 Gauze wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 19.45 fi. to 34.45 fi. From fi. to f
WELL WATER TO BE USED AS: 5 Public water supply 9 Dewatering 12 Other (Specify below) 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (1) Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted Water Well Disinfected? Yes No X 5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 19.45 ft., Dia in. to ft. Casing height below land surface ft., Weight Ibs./ft. Wall thickness or gauge No. FYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot (3) Mill slot 5 Gauze wrapped 8 Saw Cut 10 Other (specify) 5 CREEN-PERFORATED INTERVALS: From 19.45 ft. to 34.45 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 19.45 ft. to 34.80 ft. From ft. to ft. From ft. to 34.80 ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to 18 ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft.
1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 1 Signature 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 1 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 1 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 1 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 1 Other (Specify below) 2 Irrigation 4 Industrial 8 Concrete tile CASING JOINTS: Glued Clamped 2 Irrigation 2 Irrigation 3 Irrigation 3 Irrigation 4 Irrigation
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yrs Sample was submitted Water Well Disinfected? Yes No X Sample was submitted Water Well Disinfected? Yes No X Sample was submitted Water Well Disinfected? Yes No X Sample was submitted Water Well Disinfected? Yes No X Sample was submitted Water Well Disinfected? Yes No X Sample was submitted Water Well Disinfected? Yes No X Sample was submitted Water Well Disinfected? Yes No X Sample was submitted Water Well Disinfected? Yes No X Sample was submitted Water Well Disinfected? Yes No X Sample was submitted Water Well Disinfected? Yes No X Sample was submitted Water Well Disinfected? Yes No X Sample was submitted water Well Disinfected water Well Disinfected water Well Disinfected water Well Disi
Was a chemical/bacteriological sample submitted to Department? Yes No X Sample was submitted Water Well Disinfected? Yes No X
Was a chemical/bacteriological sample submitted to Department? Yes No X No X
S TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 19.45 ft., Dia in. to ft., Dia in. to ft. Casing height below land surface ft., Weight lbs./ft. Wall thickness or gauge No. FYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 2 Brass 4 Galvanized steel 6 Concrete tile CASING JOINTS: Glued Clamped 2 Continuous slot 3 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 19.45 ft. to 34.45 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 18 ft. to 34.80 ft. From ft. to ft. From ft. to ft. From ft. to ft.
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 19.45 ft., Dia in. to ft., Dia in. to ft. Casing height below land surface ft., Weight lbs./ft. Wall thickness or gauge No. PYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 19.45 ft. to 34.45 ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 18 ft. to 34.80 ft. From ft. to ft. From ft. to ft. From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete: 0-1ft Grout Intervals From 1 ft. to 18 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination:
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 19.45 ft., Dia in. to ft., Dia in. to ft. Casing height below land surface ft., Weight lbs./ft. Wall thickness or gauge No. PYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 19.45 ft. to 34.45 ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 18 ft. to 34.80 ft. From ft. to ft. From ft. to ft. From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout General state of the ft. From ft. to ft. Grout Intervals From 1 ft. to 18 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination:
(2) PVC 4 ABS 7 Fiberglass 1 Interacted A Blank casing diameter 2 in. to 19.45 ft., Dia in. to ft., Dia in. to ft. Casing height below land surface ft., Weight Ibs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 19.45 ft. to 34.45 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 18 ft. to 34.80 ft. From ft. to ft. From ft. to ft. From ft. to ft.
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 19.45 ft. to 34.45 ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 18 ft. to 34.80 ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete: 0-1ft Grout Intervals From 1 ft. to 18 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination:
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None (spen hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 19.45 ft. to 34.45 ft. From ft. to ft. From ft. Fro
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 19.45 ft. to 34.45 ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 18 ft. to 34.80 ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete: 0-1ft Grout Intervals From 1 ft. to 18 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination:
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 19.45 ft. to 34.45 ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 18 ft. to 34.80 ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete: 0-1ft Grout Intervals From 1 ft. to 18 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination:
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 8 Saw Cut 10 Other (specify) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 19.45 ft. to 34.45 ft. From ft. to ft. From f
GROUT MATERIAL: 1 Neat cement 2 Cement grout (3 Bentonite (4) Other Concrete: 0-11t Grout Intervals From 1 ft. to 18 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination:
GROUT MATERIAL: 1 Neat cement 2 Cement grout (3 Bentonite (4) Other Concrete: 0-11t Grout Intervals From 1 ft. to 18 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination:
GROUT MATERIAL: 1 Neat cement 2 Cement grout (3 Bentonite (4) Other Concrete: 0-11t Grout Intervals From 1 ft. to 18 ft. From ft. to ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination:
GROUT MATERIAL: 1 Neat cement 2 Cement grout (3 Bentonite (4) Other Concrete: 0-11t Grout Intervals From 1 ft. to 18 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination:
GROUT MATERIAL: 1 Neat cement 2 Cement grout (3 Bentonite (4) Other Concrete: 0-11t Grout Intervals From 1 ft. to 18 ft. From ft. to ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination:
GROUT MATERIAL: 1 Neat cement 2 Cement grout (3 Bentonite (4) Other Concrete: 0-11t Grout Intervals From 1 ft. to 18 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination:
Grout Intervals From 1 ft. to 18 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination:
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines / Pit privy 10 Livestock poins 14 About and water well helow)
2 Sewer lines 5 Cess poor 8 Sewage lagoon (1) I del storage
5 Wittoright bower times o people has a many
DI LICCING INTERVALS
rkowi 10 minobodio boe 22322
0 10 Grass on top, brown silty clay 10 20 Gray sandy clay, fine grained
20 25 Gray sand, fine grained
25 34.80 Gray sand, medium grained
Flushmount waiver from BOW
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1) constructed, or (3) plugged
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/30/14 and this record is true to the best of my knowledge and belief.
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Kansas Water Well Contractor's License No. 757 This Water Well Record was completed on (mo/day/year) 2/18/14 under the business name of Larsen & Associates, Inc. by (signature)
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/30/14 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 757 This Water Well Record was completed on (mo/day/year) 2/18/14