WATER WELL R		Form W			ion of Water		
Original Record 1 LOCATION OF W		Change ir	n Well Use raction		rces App. No.	Township Numb	Well ID Range Number
County: SAL	NE	LL:	ELANE 45W	SF 1/4 Section	23	T 4 S	R C E Number
2 WELL OWNER: L	ast Name:)	First: / 100 \	Street or Rura			(if unknown, distance and
Duanicas.			AMERY				r's address, check here:
Address: 517	KIRW			(511	- K	ewin	
City: SALI	MA	State: KS 2	ZIP: LOYDI		PI	ENIN	
3 LOCATE WELL	4 DEPTE	H OF COMPI	LETED WELL:	60 ft	5 Latitud	۵٠	(decimal degrees)
WITH "X" IN SECTION BOX:	Depth(s) Gr	roundwater End	countered: 1)3	ft.			(decimal degrees)
N SECTION BOX.	2)	ft. 3).	ft., or 4)	Dry Well	Datum: [□ WGS 84 □ NAI	D 83 NAD 27
	WELL'S S	TATIC WATE	R LEVEL:de easured on (mo-day	VE) QC=2X-		or Latitude/Longitude	
NW NE	above 1	land surface, me	easured on (mo-day easured on (mo-day	-yr)	☐ GPS	(WAAS enabled?)
			r was		☐ Lane	d Survey Topogra	
W E	after		ımping 3.0 er was		Onli	ine Mapper:	
SW SE	after		mping				
	Estimated Y	ـــــــــــــــــــــــــــــــــــــ	gpm	0.			. Ground Level TOC
S	Bore Hole		in. to 4D				GPS Topographic Map
1 mile 7 WELL WATER TO	DE HEED		in. to	π.			
1. Domestic:			Supply: well ID		10. □ Oil F	ield Water Supply: le	ease
☐ Household	6.	Dewatering:	how many wells?	•••••	 Test Ho 	le: well ID	
Lawn & Garden			arge: well ID			d □ Uncased □ 0	
Livestock 2. Irrigation			well ID Remediation: well I			mal: how many bores ed Loop Horizont	
3. ☐ Feedlot		Air Sparge	☐ Soil Vapor				ischarge Inj. of Water
4. Industrial		Recovery	☐ Injection		13. 🔲 Othe	r (specify):	
Was a chemical/bacter	~	-	ed to KDHE? 🗆	Yes No	If yes, date s	ample was submitte	ed:
Water well disinfected?				CACDI	C IODITC.	V al 1 E al	
8 TYPE OF CASING USED: Steel PVC Other							
Casing diameter (5)	in to	√⊘ f D	iameter	in to	ft Diamet	er in to	ff Interded
Casing height above land	in. to surface 2	5	iameter انعلانا	in. to	ft., Diamet	er in. to	ft.
Casing height above land a TYPE OF SCREEN OF	in. to	5 ft., D D in. TION MATE	iameter Weightاری RIAL:	in. to	ft., Diamet Wall thickne	erin. to ess or gauge No. £.D	
Casing height above land of TYPE OF SCREEN OF Steel ☐ Stain	in. to	D ft., D. D in. TION MATE ☐ Fibergla	iameter	in. to	ft., Diamet Wall thickne	erin. to ess or gauge No. £.D	ft.
Casing height above land of TYPE OF SCREEN OF Steel ☐ Stain	in. to	Dft., D. Din. TION MATE ☐ Fibergla ☐ Concrete	iameter	in. to	ft., Diamet Wall thickne	erin. to ess or gauge No. £.D	
Casing height above land s TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot	surface 2 RERFORA RIPERFORA RIPE	TION MATE Fibergla Concrete NINGS ARE	iameter	in. to	ft., Diamet Wall thickne Other	er	ft.
Casing height above land s TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot	surface 2 RERFORA RIPERFORA RIPE	TION MATE Fibergla Concrete NINGS ARE	iameter	in. to	ft., Diamet Wall thickne Other	er	ft.
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI	surface 2 R PERFORA class Steel vanized Steel ATION OPE Mill Slot Key Punc ED INTERV	TION MATE Fibergla Concrete ENINGS ARE Gauz ched Wire ALS: From	iameter Weight	in. to	ft., Diamet Wall thickne Other illed Holes [one (Open Hol ft. to	er	ft
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG 9 GROUT MATERIA	surface 2 PERFORA nless Steel vanized Steel ATION OPE Mill Slot Key Punc ED INTERV CK INTERV L: Neat	TION MATE Fibergla Concrete ENINGS ARE Wire ALS: From	iameter Weight	in. to	ft., Diamet Wall thickne Other illed Holes [one (Open Hol ft. to her	er	ft. 6
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From	surface 2 R PERFORA hless Steel ranized Steel ATION OPE Key Punc ED INTERV KINTERV L: Neat	TION MATE	iameter Weight	in. to	ft., Diamet Wall thickne Other illed Holes [one (Open Hol ft. to her	er	ft. 6
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possible	surface 2 R PERFORA filess Steel vanized Steel ATION OPE Mill Slot Key Punc ED INTERV CK INTERV L: Neat c contaminat	TION MATE Fibergla Concrete ENINGS ARE Gauz ched Wire ALS: From cement Co	iameter Weight	in. to	ft., Diamet Wall thickne Other illed Holes [one (Open Hol ft. to her	er	ft. ft. to
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From	surface 2 R PERFORA hless Steel ranized Steel ATION OPE Mill Slot Key Punc ED INTERV CK INTERV L: Neat c contaminat	TION MATE	iameter Weight	in. to	ft., Diamet Wall thickne Other illed Holes [one (Open Hol ft. to her	er	ft. 6
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lines	surface 2 R PERFORA hless Steel ranized Steel ATION OPE Key Punc ED INTERV CK INTERV L: Neat c contaminat hes	TION MATE Fibergla Concrete ENINGS ARE ALS: From Cement Co Co ft Coss Pool Seepage Pit	iameter Weight	in. to	ft., Diamet Wall thickne Other illed Holes [one (Open Hol ft. to her ft., Fromivestock Pens fuel Storage fertilizer Storage	er	ft. ft. to
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lines	surface 2 R PERFORA hless Steel ranized Steel ATION OPE Key Punc ED INTERV CK INTERV L: Neat c contaminat hes	TION MATE Fibergla Concrete ENINGS ARE ALS: From Cement Co Co ft Coss Pool Seepage Pit	iameter Weight	in. to	ft., Diamet Wall thickne Other illed Holes [one (Open Hol ft. to her ft., Fromivestock Pens fuel Storage fertilizer Storage	er	ft. ft. to
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines	surface 2 R PERFORA nless Steel vanized Steel ATION OPE Mill Slot Key Punc ED INTERV CK INTERV L: Neat Contaminat nes	TION MATE Fibergla Concrete ENINGS ARE ALS: From Cement Co Co ft Coss Pool Seepage Pit	iameter Weight	in. to	ft., Diamet Wall thickne Other Other illed Holes [one (Open Hol ft. to her ft. y ft., From ivestock Pens fuel Storage fertilizer Storage	er	ft. ft. to
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO	surface 2 R PERFORA nless Steel vanized Steel ATION OPE Mill Slot Key Punc ED INTERV L: Neat Contaminat nes	TION MATE Fibergla Concrete Concrete Fibergla Concrete Concrete Fibergla Concrete Fibergla Concrete Fibergla Concrete Fibergla Concrete Concrete	iameter Weight	in. to	ft., Diamet Wall thickne Other Other illed Holes [one (Open Hol ft. to her ft. yr ft., From civestock Pens fuel Storage fertilizer Storage	er	ft. ft. to
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO 2 2 2 3	in. to	TION MATE Fibergla Concrete Concrete Fibergla Concrete Fibergla Concrete Fibergla Concrete Fibergla Concrete Fibergla Concrete Fibergla Concrete Call From Concrete Concre	iameter Weight	in. to	ft., Diamet Wall thickne Other Other illed Holes [one (Open Hol ft. to her ft. yr ft., From civestock Pens fuel Storage fertilizer Storage	er	ft. ft. to
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO 2 2 2 3	in. to	TION MATE Fibergla Concrete Concrete Fibergla Concrete Fibergla Concrete Fibergla Concrete Fibergla Concrete Fibergla Concrete Fibergla Concrete Call Concrete Co	iameter Weight	in. to	ft., Diamet Wall thickne Other Other illed Holes [one (Open Hol ft. to her ft. yr ft., From civestock Pens fuel Storage fertilizer Storage	er	ft. ft. to
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO 2 2 2 3	in. to	TION MATE Fibergla Concrete Concrete Fibergla Concrete Concrete	iameter Weight	in. to	ft., Diamet Wall thickne Other Other illed Holes [one (Open Hol ft. to her ft. yr ft., From civestock Pens fuel Storage fertilizer Storage	er	ft. ft. to
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG OCHORAL Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? TO FROM TO OCHORAL STAIN A STAIN STAIN SEWER LINE OCHORAL STAIN OC	in. to	TION MATE Fibergla Concrete Concrete Fibergla Concrete Concrete	iameter Weight	in. to	ft., Diamet Wall thickne Other Other illed Holes [one (Open Hol ft. to her ft. yr ft., From civestock Pens fuel Storage fertilizer Storage	er	ft. ft. to
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO 2 2 2 3	in. to	TION MATE Fibergla Concrete Concrete Fibergla Concrete Concrete	iameter Weight	in. to	ft., Diamet Wall thickne Other Other illed Holes [one (Open Hol ft. to her ft. yr ft., From civestock Pens fuel Storage fertilizer Storage	er	ft. ft. to
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO 2 2 2 3	in. to	TION MATE Fibergla Concrete Concrete Fibergla Concrete Concrete	iameter Weight	in. to	ft., Diamet Wall thickne Other Other illed Holes [one (Open Hol ft. to her ft. yr ft., From civestock Pens fuel Storage fertilizer Storage	er	ft. ft. to
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GRAVEL PAG GRAVEL PAG GRAVEL PAG GRAVEL PAG GRAVEL PAG OF GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? TO FROM TO O 2 2 31 32 36 36 39 30 30 30 30 30 30 30 30 30	in. to	S.C ft., D. D in. TION MATE Fibergla Concrete ENINGS ARE OAS Gauz thed Wire ALS: From Call From	iameter Weight	in. to	ft., Diamet Wall thickne Other illed Holes	er	ft. ft. to ft
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GRAVEL PAG GRAVEL PAG GRAVEL PAG GRAVEL PAG GRAVEL PAG OF GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? TO FROM TO O 2 2 31 32 36 36 39 30 30 30 30 30 30 30 30 30	in. to	S.C ft., D. D in. TION MATE Fibergla Concrete ENINGS ARE OAS Gauz thed Wire ALS: From Call From	iameter Weight	in. to	ft., Diamet Wall thickne Other illed Holes	er	ft. ft. to ft
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GRAVEL PAG GRAVEL PAG GRAVEL PAG GRAVEL PAG GRAVEL PAG OF GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? TO FROM TO O 2 2 31 32 36 36 39 30 30 30 30 30 30 30 30 30	in. to	S.C ft., D. D in. TION MATE Fibergla Concrete ENINGS ARE OAS Gauz thed Wire ALS: From Call From	iameter Weight	in. to	ft., Diamet Wall thickne Other illed Holes	er	ft.
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PACE GRAVEL PA	Mill Slot, CHANDING COR LAND OR LAND	ALS: From Compatible Gauzand Gauz	iameter Weight	in. to	ft., Diamet Wall thickne Wall thickne Wall thickne Other illed Holes [one (Open Hole ft. to ft., From ft., From ivestock Pens fuel Storage fertilizer Storage fertilizer Storage ford was comp	constructed, recorrue to the best of moleted on (mo-day-y-	ft. ft. to

KSA 82a-1212

Revised 9/10/2012

Visit us at http://www.kdheks.gov/waterwell/index.html