WATER WELL RE	CORD X.S	A3 Form W	/WC-5	Di	ivision of Wate	r Resources App. N	Y0	
1 LOCATION OF WA		Fraction					Range Number	
County: SALIN		SE 45W 4NV	1/4 1/4				R 3 □E ØW	
Street/Rural Address				Globa	el Positioning	System (GPS) i	nformation:	
from nearest town or intersection: If at owner's address, check here . Latitude:38° 50' 56" (in decimal degree								
501 N. SANTE FE					Global Positioning System (GPS) information: Latitude: 38. 56. 1. (in decimal degrees) Longitude: 97. 36. 34. 4. (in decimal degrees)			
					Elevation: 12921			
SALINA KS 67401					Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OV	WNER: MATA	don CATTLE	Co.	Calle	ation Mathada			
2 WATER WELL OWNER: MATA don CATTLE Co. RR#, Street Address, Box #: 4111 E. 37 Th St. North City, State, ZIP Code: 4111 E. 37 Th					☐ GPS unit (Make/Model:			
City, State, ZIP Code	14 15 64 3	HA, KS 6	ס פב ר		Digital Map/Pt	roto, 🔲 Topograph	ic Map, Land Survey	
1 LOCATE WILL	1] 5-15 m, [] >15 m	
3 LOCATE WELL WITH AN "X" IN	4 DEPTH OF	COMPLETED WEL	т.	30	ft			
SECTION BOX:		lwater Encountered					(3) ft.	
N N		C WATER LEVEL						
	Pump test data: Well water was ft. after hours pumping gpm EST. YIELD gpm. Well water was ft. after hours pumping gpm							
1 1 1 1	Doro Holo Diameter & in to 30' ft and in to ft							
W X E							Injection well	
Demostic Descript Coll field wroter manufact Demostrating College (Secrify below)								
SW - SE -								
Was a chemical/bacteriological sample submitted to Department? Yes No								
S If yes, mo/day/yr sample was submitted								
1 mile Water well disinfected? ☐ Yes ☑ No								
5 TYPE OF CASING USED: Steel PVC Other STAIN IESS STEE								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter 4" in to 5 ft Diameter in to ft Diameter in to ft								
Casing diameter 4" in to 5 ft., Diameter in to ft., Diameter in to ft. Casing height above land surface 2 in., Weight lbs./ft., Wall thickness or gauge No. 304								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel Stainless Steel ☐ PVC ☐ Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot								
□ Louvered shutter □ Key punched □ Wire wrapped □ Saw cut □ Other (specify) SCREEN-PERFORATED INTERVALS: From								
SCREEN-PERPORATED INTERVALS: From								
From								
From ft. to ft. From ft. to ft.								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Class H. Silica Flour. Grout Intervals: From Other Class H. Silica Flour.								
Grout Intervals: From								
What is the nearest source of possible contamination: ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)								
Sewer lines	Cesspool	Sewage lagoon	Fuel stora	•	Abandone	water well	, -	
☐ Watertight sewer		it Feedyard	Fertilizer		Oil well/ga		J/A	
Direction from well					ell		<i>,</i>	
FROM TO	LITHOLOG	IC LOG	FROM	TO	LITHO. L	OG (cont.) or PLU	UGGING INTERVALS	
0' 1' 00	NCROTE					4 11 12 12 12		
1' 16' F.11		ome concrete						
	unics							
16' 27' 8H		as / Brown						
3 3 3 5 5	7	7 7 3. 3. 10						
27' 30' SAM	10							
21 2013			1			.,		
			1					
			 					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, □ reconstructed, or □ plugged								
under my jurisdiction and was completed on (mo/day/year) 913/2014 and this record is true to the best of my knowledge and belief								
under my jurisdiction and was completed on (mo/day/year)								
under the husiness name	of Cannin F	Selvia	L	hv (e	ignature)	1777	Z	
INSTRUCTIONS: Use types	writer or ball point ben	PLEASE PRESS FIRML	Y and PRINT c	learly. Ple	ase fill in blank	and check the confec	answers. Send one copy to	
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suit e 429, Topeka, Kansas 66, 12-1367.								
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5 100 for each constructed well. Visit us at								

