WATER WELL RECORD ¥ 0 ℃ Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL: Fraction	Section Number Township No. Range Number
County: SALINE SE 45W 4NW 4 4	
Street/Rural Address of Well Location; if unknown, distance & direction	Clobal Positioning System (CPS) information:
from nearest town or intersection: If at owner's address, check here .	Latitude: \$6 50 56 \(\lambda\) (in decimal degrees) Longitude: 970 3€ 34' \(\lambda\) (in decimal degrees)
501 N. SANTE FF	Longitude: 976 36 34 10 (in decimal degrees)
Salina KS 67401	Elevation: 12931
2 WATER WELL OWNER: 4 October Co.	Datum: WGS 84, NAD 83, NAD 27
2 WATER WELL OWNER: MATA don CATTLE Co. RR#, Street Address, Box #: 4111 E. 37 LA ST. NORTH	Collection Method: I - Phone GPS unit (Make/Model: I - Phone)
City, State, ZIP Code 4111 E. 31.	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey
City, State, ZIP Code Wich: ta KS 67220	Est. Accuracy:
3 LOCATE WELL	
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 50	t.
SECTION BOX: Depth(s) Groundwater Encountered (1)	ft. (2) ft. (3) ft ft below land surface measured on mo/day/yr?/\(\frac{1}{20.1\frac{1}{20.1}}\).
WELL STATIC WATER LEVEL. 33	ft. after hours pumping gpm
FST VIFID onm Well water was	ft after hours pumping gpm
W Self-water was	ft. after
WELL WATER TO BE USED AS: Public wat	ter supply Geothermal Injection well
Domestic Deadlet Delifield wet	er supply Dewatering Other (Specify below)
	wn & garden [Monitoring well .E. T.R.A.C.T. i.o.]
Was a chemical/bacteriological sample submitted to	
S If yes, mo/day/yr sample was submitted	
Water well disinfected? ☐ Yes ☑ No	
5 TYPE OF CASING USED: Steel PVC Other\$7.	AIN JESS STEET
CASING IOINTS: Glued Clamped Welded M Threader	d
Casing diameter	to ft Diameter in. to ft.
Casing height above land surface. 2! in., Weight	lbs./ft., Wall thickness or gauge No. 30.4
TYPE OF SCREEN OR PERFORATION MATERIAL:	,
Steel Stainless Steel PVC	Other (Specify)
Brass Galvanized Steel None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE: GLauge Wrapped Torch cut Drilled holes None (open hole)	
Louvered shutter	Other (specify)
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut SCREEN-PERFORATED INTERVALS: From	ft From ft to ft
From ft. to	ft. Fromft. toft.
GRAVEL PACK INTERVALS: From	ft., From ft. to ft.
From ft. to	ft., From ft. to ft.
6 GROUT MATERIAL: Neat cement Cement grout Benton	nite Other CLASS HI SILICA Flour GROUT
6 GROUT MATERIAL: Neat cement Cement grout Benton Grout Intervals: From	ft. to
What is the nearest source of possible contamination:	
Septic tank	
Sewer lines Cesspool Sewage lagoon Fuel storag Watertight sewer lines Seepage pit Feedyard Fertilizer st	
	torage Oil well/gas well from well
FROM TO LITHOLOGIC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
O' 6" CONCRETE	LITTIO. LOG (COIR.) OF TECOGRAPH INTERVALS
6" 271 Brown Sity Chay 10104	
27' DSU SAMO	
g ou grade	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water	er well was Constructed. Treconstructed or I plugged
under my jurisdiction and was completed on (mo/day/year) 1161.29 and this record is true to the best of my knowledge and belief.	
Kansas Water Well Contractor's License No 7.93 This Water Well R	ecord was completed on mg/gay/year?
under the business name of Cahou Yump Selvice	by (signature)
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT cle	early. Please fill in blanks and paeck the correct answers. Send one copy to
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 424, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at	

