WATER WELL RE	CORD XS	C4 Form W	VWC-5	Division of Wate	r Resources App. No.	
1 LOCATION OF WATER WELL: Fraction			Section Number	Township No.	Range Number	
County: SAINE SE 45W 4NW 4			12	T /9//S/	R 3 LE MW	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here						
	owner's address, chec	Global Positioning System (GPS) information: Latitude: 38,50,56,6,6,6,6,6,6,6,6,6,6,6,6,6,6,6,6,6				
501 N. SANTE FF				Elevation: 1227' (in decimal degrees)		
SALINA KS 67401				Datum: WGS 84, NAD 83, NAD 27		
2 WATER WELL OWNER: MATA don CATILE Co. Collection Method:						
2 WATER WELL OWNER: MATA don CATTLE Co. RR#, Street Address, Box #: City, State, ZIP Code : 4111 E. 37 Th St. North				GPS unit (Make/Model: I Phone)		
City, State, ZIP Code Digital Map/Photo, Topographic Map, Land Survey						
3 LOCATE WELL					э ш, 🗀 э-э ш, 🗀 -	-15 ш, 🔲 > 15 ш
WITH AN "X" IN						
SECTION BOX:	Depth(s) Groundwater Encountered (1)					
N	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr					
	Pump test data: Well water was ft. after hours pumping gpm					
W EST. YIELDgpm. Well water wasft. afterhours pumpinggpm. Well water wasft., andin. toft.						
W X E	WELL WATER	TO BE USED AS:	Public water	er supply	othermal	jection well
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below)						
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well . CATRACT. LOA)						
Was a chemical/bacteriological sample submitted to Department? Yes No						
S If yes, mo/day/yr sample was submitted						
Water went distincted: [] 165 by 140						
5 TYPE OF CASING USED: Steel PVC Other STAIN IFS S STEE!						
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter in. to ft., Diameter in. to ft., Diameter ft., Diameter						
Casing diameter						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
Steel Stainless Steel PVC Other (Specify)						
Brass Galvanized Steel None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot						
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From						
From						
From						
From						
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Class H Silica Flour GAOUT						
Grout Intervals: From						
What is the nearest source of possible contamination:						
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well						
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well						
Direction from well .				from well		
FROM TO	LITHOLOG	IC LOG	FROM	TO LITHO. LO	OG (cont.) <u>or</u> PLUC	GING INTERVALS
	wente					
1' 27' 8-1	Ø 1	OCHY	+			
22/ 20/ 0	Brown					
27' 30' S	ano.					
			 			
			1			
			1			
		<u> </u>				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was -constructed, - reconstructed, or - plugged						
under my jurisdiction and was completed on (mo/day/year) 1.4.2.1.4 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No						
under the business name	of languy	rump Delli	J.U.L.	by (signature)	J. J. W	Sand and a
INSTRUCTIONS: Use typewriter or ball point pan. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and seek the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.						
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at						

