WATER WELL RECORD $ ot subseteq ot ot ot ot ot ot ot ot ot ot$	rm WWC-5 Division of Water Resources App. No.
1 LOCATION OF WATER WELL: Fraction	, Section Number Township No Range Number
County: SALINE SE 45W	4 4 4 4 4 4 4 4 4 4
Street/Rural Address of Well Location; if unknown, di	
from nearest town or intersection: If at owner's address	is, check here . Latitude:
501 N. SANTE FE	Longitude: 97. 36
SAliNA KS 67401	Elevation:/233/
2 WATER WELL OWNER:	Datum: WGS 84, NAD 83, NAD 27 Collection Method:
2 WATER WELL OWNER: MATA dan CATILE Co. RR#, Street Address, Box #: City, State, ZIP Code 2 WATER WELL OWNER: MATA dan CATILE Co. Collection Method: GPS unit (Make/Model: Phone) Digital Map/Photo, Topographic Map, Land Survey	
City, State, ZIP Code : 4111 E. 3	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey
City, State, ZIP Code Wick ita KS	67290 Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m
3 LOCATE WELL	30′
WITH AN "X" IN 4 DEPTH OF COMPLETE	D WELL ft.
	tered (1) ft. (2) ft. (3) ft.
WELL SSIATIC WATER LI	EVELft. below land surface measured on mo/day/yr
Pump test data: W	fell water was ft. after hours pumping gpm
Doro Holo Diameter X	ell water wasft. after
	AS: Public water supply Geothermal Injection well
Domestic Feedlet	Oil field water supply Dewatering Stother (Specify below)
	Domestic-lawn & garden Monitoring well .EATRACT. 1.00
	I sample submitted to Department? Yes X No
	was submitted
1 mile Water well disinfected? ☐ Ye	
5 TYPE OF CASING USED: Steel PVC	•
CASING IOINTS: Glored Grand G We	alded M Threaded
CASING JOINTS: Glued Clamped Welded Threaded	
Casing diameter 4" in to 5 ft., Diameter in to ft., Diameter in to ft. Casing height above land surface 24" in., Weight lbs./ft., Wall thickness or gauge No. 304	
TYPE OF SCREEN OR PERFORATION MATERIAL:	
☐ Steel Stainless Steel ☐ PVC ☐ Other (Specify)	
Brass Galvanized Steel None used	I (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	
Continuous slot Mill slot Gauze wrap	oped Torch cut Drilled holes None (open hole)
☐ Louvered shutter ☐ Key punched ☐ Wire wrapp	ped Saw cut Other (specify)
SCREEN-PERFORATED INTERVALS: From	ft. to
From	ft. to
GRAVEL PACK INTERVALS: From	ft. to ft. to ft.
From	ft. to ft. ft.
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other CLASS H. Silica Flour Grout Intervals: From O. ft. to 3. ft., From ft. to ft., From ft. to ft.	
What is the nearest source of possible contamination:	
Septic tank Lateral lines Pit privy	Livestock pens
Sewer lines Cesspool Sewage	lagoon Fuel storage Abandoned water well
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard	
Direction from well	Distance from well
FROM TO LITHOLOGIC LOG	FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0 61 CONCRETE	
61 27' SHy Chy Chy RMON	m)
271 301 Sour	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year)	
under my jurisdiction and was completed on (mo/day/year)	
Kansas Water Well Contractor's License No	
under the business name of Canay Hump Service by (signature)	
INSTRUCTIONS: Use typewriter or ball point/pen. PLEASE PRESS	S FIRMLY and PRINT clearly. Please fill in blanks and cheef the correct answers. Send one copy to vater, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612 1367.
	P and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at

httn://www.kdheks.onv/waterwell/index.html

