WATER WELL RECORD $\checkmark$ D - D ? Form WWC-5 Division of Water Resources App. No.	
1 LOCATION OF WATER WELL: Fraction . Section Number Township No. Range Number	
County: SALINE SE 45W 4NW 4 12 T 14 S R 3 DE S	Zw
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:	•
from nearest town or intersection: If at owner's address, check here . Latitude: 38° 56° 56° 50° (in decimal degree Longitude: 97° 36° 35° (in decimal degree Longitude: 97° 36° (in decimal degree Longitude: 97° (in decimal degree Longitud	ees) ees)
SAlina KS 67401 Elevation: 1222	
2 WATER WELL OWNER: Martin des Cott   Collection Method:	
RR#, Street Address, Box #: The ST North GPS unit (Make/Model: F-Phone	)
	vey
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL SO	
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 5.0 ft.	
SECTION BOX: Depth(s) Groundwater Encountered (1)	.π.
WELL SSIATIC WATER LEVEL 30 below land surface measured on mo/day/y127272727.	?. <b>7</b> .
Pump test data: Well water was	bm
W -NW - NE - EST. YIELD gpm. Well water was ft. after hours pumping gr	om
W X   E   Bore Hole Diameter	
Demostric Confession Collected water supply Conditional Confession Consistent Confession Consistent Confession	
Was a chemical/bacteriological sample submitted to Department? Yes No  If yes, mo/day/yr sample was submitted	
Water well disinfected? ☐ Yes ✓ No	
5 TYPE OF CASING USED: Steel PVC Other STAIN IFSS STEEL	
CASING JOINTS:  Glued  Clamped  Welded  Threaded	_
Casing diameter	. ft.
Casing height above land surface	
TYPE OF SCREEN OR PERFORATION MATERIAL:	
☐ Steel   ☐ Stainless Steel ☐ PVC ☐ Other (Specify)	
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:	
Continuous slot	
Louvered shutter  Key punched  Wire wrapped  Saw cut  Other (specify)	
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)  SCREEN-PERFORATED INTERVALS: From 3.8	ft.
From ft. to ft. From ft. to	ft.
From	ft.
From	
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Class H. Silica Flour. Ga	OUT
Grout Intervals: From O' ft. to 36' ft., From ft. to ft., From ft. to	ft.
What is the nearest source of possible contamination:	
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)	
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well	
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well	
Direction from well	
FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTERVA	ALS
0' 6" CONCRETE	
6" 27' Brown Silty Clay Iclay	
27' 80' 8AMO	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugge	:d
under my jurisdiction and was completed on (mo/day/year) 91.6/22/4 and this record is true to the best of any knowledge and believe	øf.
Kansas Water Well Contractor's License No. 793 This Water Well Record was completed on productive and 124	14
under the business name of Carroy Pump Selvice by (signature)	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, or plugge under my jurisdiction and was completed on (mo/day/year)	y to

