WATER WELL R	ECORD XD EY	Form WWC-5	Division of W	ater Resources App. No		
1 LOCATION OF V				Township No.		
		V 4 NW 4 1	12	T 14 (S)	R 3 □E ZIW	
Street/Rural Addres	s of Well Location; if unknown,		Global Position	ing System (GPS) inf	formation:	
from nearest town	or intersection: If at owner's add	Latitude:3.8	5 0 56%	formation: (in decimal degrees) (in decimal degrees)		
501 N.	Longitude: .9.?	36 350	∴ (in decimal degrees)			
Salina	Elevation:	2 221				
SALINA KS 6740/ Batum: WGS 84, NAD 83, NAD 27 WATER WELL OWNER: MATER don CATTLE Co. Collection Method:						
RR#, Street Address, Box #: RR#, Street Address, Box #: GPS unit (Make/Model: I-Phone)						
Charles 7TD Code . The code .						
City, State, ZIP Code Wick: HA KS 67220 Digital Map/Photo, Topographic Map, Land Survey Est. Accuracy: <3 m, 3-5 m, 5-15 m, >15 m						
3 LOCATE WELL						
WITH AN "X" IN	4 DEPTH OF COMPLET	ED WELL 30				
SECTION BOX:	Depth(s) Groundwater Encountered (1)					
14	WELL'S STATIC WATER LEVEL. 3ft. below land surface measured on mo/day/yr.77					
	Pump test data: Well water was					
NW NE						
w x	E Bore Hole Diameter					
SW SE						
Was a chemical/bacteriological sample submitted to Department? Yes No						
S If yes, mo/day/yr sample was submitted						
1 mile Water well disinfected? ☐ Yes ☑ No						
5 TYPE OF CASING USED: Steel PVC Other STAIN IESS STEEL						
CASING JOINTS: Glued G Clamped Welded M Threaded						
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter in. to ft., Diameter in. to ft.						
Casing height above land surface 34' in., Weight						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
☐ Steel Stainless Steel ☐ PVC ☐ Other (Specify)						
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft.						
	EL INTERVALS. E Vi	apped Saw cut	Other (specify)	Δ		
From ft to ft From ft to ft						
From. ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 39' ft. to 50' ft., From ft. to ft.						
From						
6 GROUT MATERIAL: Neat cement Cement grout Rentonite 20 Other Class #1 Silica Flour GAOUT						
Grout Intervals: From Of the to 3.7 ft., From the to the ft., From the to the ft.						
What is the nearest source of possible contamination:						
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)						
Sewer lines	☐ Cesspool ☐ Sewag			ned water well		
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well						
Direction from well	An artist to the second		from well		,	
FROM TO	LITHOLOGIC LOG	FROM	TO LITHO.	LOG (cont.) or PLUC	GGING INTERVALS	
	nucheto	,				
6 0 1014	OWN SHYCKY (C)	AX				
27' 52' 5	AND					
7 CONTRACTORIS	OR LANDOWNERS CERTIFIE	ELCATION. This	12 130		-t-1	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year)						
Kansas Water Well Contractor's License No						
under the business nam		D. Selvice.			7?+5~7+17	
	pewriter or ball point pen. PLEASE PRI				Send one conv to	
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, opeka, Kansas 66612 367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5,000 or each constructed well. Visit us at						

