WATER	WELL RI	ECORD	Form WV	Division of Wate	r Resources App. No	o. L			
1 LOCATION OF WATER WELL:			Fraction		Section Number		Range Number	er	
County: Saline			SE 1/4 NE 1/4 NE			T 14 S		∑ ⊘ W	
			f unknown, distance &	Global Positioning System (GPS) information:					
from nearest town or intersection: If at owner's address, check here .					Latitude: .38.81084				
1900 S. 9th Street Salina, KS 67401					Longitude: 97.61329 (in decimal degrees) Elevation: 1235.31				
					Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27				
2 WATER WELL OWNER: Suburban TV					Collection Method:				
RR#, Street Address, Box #: 1900 S. 9th St					GPS unit (Make/Model:)				
City, State, ZIP Code : Salina, KS 67401					☐ Digital Map/Photo, ☐ Topographic Map, ☑ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m				
2 1004	TOTAL SECTION OF			Est. Accuracy:	3 m, ∐ 3-5 m, ∐	5-15 m, ∐>15	m		
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 40.0 ft.									
1	SECTION BOX: Depth(s) Groundwater Encountered (1), 27.61, ft. (2), ft. (3), ft.								
	N WELL'S STATIC WATER LEVEL. 27.61ft. below land surface measured on mo/day/yr								
	Pump test data: Well water wasft. after hours pumping								
-NW -NF EST. YIELDgpm. Well water wast. after nours pumping gpm								gpm	
w	W E Bore Hole Diameter								
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well									
SW SE								below)	
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☑ Monitoring well									
S If yes, mo/day/yr sample was submitted									
mile Water well disinfected? \[\text{Yes} \] No									
5 TYPE OF CASING USED: Steel PVC Other									
CASING JOINTS: Glued Clamped Welded Threaded									
Casing diameter 2.0 in. to .25.0 ft., Diameter in. to ft.									
Casing height above land surface3.72									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel									
Brass Galvanized Steel None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Gauze wrapped Torch cut None (open hole)									
Continuous slot									
SCREEN-PERFORATED INTERVALS: From									
From									
GRAVEL PACK INTERVALS: From									
From									
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other									
Grout Intervals: From 1.0 ft. to 23.0 ft., From ft. to ft., From ft. to ft., From ft. to ft., From ft. to ft.									
	ne nearest sou Septic tank	irce of possible cont		Livestock	pens	e storage 🗖 Oti	her (specify belov	w)	
	Sewer lines	Cesspool	Sewage lagoon				ner (specify below	",	
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well									
					from well Lust sit		<u></u>		
FROM	TO	LITHOLOG	GIC LOG	FROM	TO LITHO, L	OG (cont.) <u>or</u> PLU	<u>JGGING INTE</u>	RVALS	
		crete							
		clavev		<u> </u>					
		, silty							
 		, silty		+ +					
		Clayey d, very fine							
		, silty			MW8				
		, silty			INIAAO				
20	10 0.4,	, 0.1.1			·				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged									
under my jurisdiction and was completed on (mo/day/year) .09-24-2015 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 594 This Water Well Record was completed on pro/day/594/51-02-2015 under the business name of Coranco Great Plains, Inc. by (signature)									
INSTRUC	TIONS: Use ty	pewriter or ball point pe	n. PLEASE PRESS FIRML	and <u>PRINT</u> cl	early. Please fill in blank	s and check the correct	t answers. Send on	ie copy to	
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at									

http://www.kdheks.gov/waterwell/index.html