

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number																																																																																					
County: Saline		NE ¼ NW ¼ NW ¼		13		T 14 S		R 3 EW																																																																																					
Distance and direction from nearest town or city street address of well if located within city? 2118 Planet Ave., Salina																																																																																													
2 WATER WELL OWNER: Jim's Formal Wear																																																																																													
RR#, St Address, Box # : 2118 Planet Avenue					Board of Agriculture, Division of Water Resources																																																																																								
City, State, ZIP Code : Salina, Kansas 67401					Application Number:																																																																																								
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 50 ft ELEVATION: 1241.45																																																																																											
		Depth(s) Groundwater Encountered 1. ft 2. ft 3. ft																																																																																											
		WELL'S STATIC WATER LEVEL 24.37 ft below land surface measured on mo/day/yr 5/19/2016																																																																																											
		Pump test data: Well water was NA ft after hours pumping gpm																																																																																											
		Est Yield NA gpm: Well water was ft after hours pumping gpm																																																																																											
		Bore Hole Diameter 8 in. to 50 ft, and in. to ft																																																																																											
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well																																																																																													
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)																																																																																													
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well																																																																																													
Was a chemical/bacteriological sample submitted to Department? Yes.....No✓; If yes, mo/day/yr sample was submitted																																																																																													
Water Well Disinfected? Yes No✓																																																																																													
5 TYPE OF BLANK CASING USED:																																																																																													
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped																																																																																													
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded																																																																																													
7 Fiberglass Threaded. ✓																																																																																													
Blank casing diameter 2 in. to 40 ft, Dia in. to ft, Dia in. to ft																																																																																													
Casing height above land surface -4.08 in., weight lbs./ft Wall thickness or gauge No. Sch. 40																																																																																													
TYPE OF SCREEN OR PERFORATION MATERIAL																																																																																													
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement																																																																																													
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)																																																																																													
9 ABS 12 None used (open hole)																																																																																													
SCREEN OR PERFORATION OPENINGS ARE:																																																																																													
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)																																																																																													
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes																																																																																													
7 Torch cut 10 Other (specify)																																																																																													
SCREEN-PERFORATED INTERVALS: From 40 ft to 50 ft, From ft to ft																																																																																													
GRAVEL PACK INTERVALS: From 38 ft to 50 ft, From ft to ft																																																																																													
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete																																																																																													
Grout intervals: From 0 ft to 2 ft, From 2 ft to 38 ft, From ft to ft																																																																																													
What is the nearest source of possible contamination:																																																																																													
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well																																																																																													
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well																																																																																													
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)																																																																																													
13 Insecticide storage																																																																																													
Direction from well? How many feet?																																																																																													
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>5.75</td> <td>Hydrovacuumed,</td> <td></td> <td></td> <td></td> </tr> <tr> <td>5.75</td> <td>10</td> <td>Silt, sandy (vf), some clay, Mod. Yellow Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>10</td> <td>16.3</td> <td>Clay, silty, Dark Yellow Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>16.3</td> <td>18.5</td> <td>Silt, sandy (vf), some clay, Mod. Yellow Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>18.5</td> <td>20</td> <td>Clay, silty, Dark Yellow Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>20</td> <td>23.5</td> <td>Clay, Pale Yellow Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>23.5</td> <td>25</td> <td>Clay, Pale Yellow Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>25</td> <td>30</td> <td>Clay, Dark Yellow Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>30</td> <td>32</td> <td>Silt, sandy (f), Pale Yellow Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>32</td> <td>40</td> <td>Clay, silty, Dark Yellowish Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>40</td> <td>43.5</td> <td>Sand, f-m, silty, Light Gray to Gray Orange</td> <td></td> <td></td> <td></td> </tr> <tr> <td>43.5</td> <td>45</td> <td>Sand, f-c, Dark Yellow Orange</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>MW-8, Flushmount</td> </tr> </tbody> </table>										FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	5.75	Hydrovacuumed,				5.75	10	Silt, sandy (vf), some clay, Mod. Yellow Brown				10	16.3	Clay, silty, Dark Yellow Brown				16.3	18.5	Silt, sandy (vf), some clay, Mod. Yellow Brown				18.5	20	Clay, silty, Dark Yellow Brown				20	23.5	Clay, Pale Yellow Brown				23.5	25	Clay, Pale Yellow Brown				25	30	Clay, Dark Yellow Brown				30	32	Silt, sandy (f), Pale Yellow Brown				32	40	Clay, silty, Dark Yellowish Brown				40	43.5	Sand, f-m, silty, Light Gray to Gray Orange				43.5	45	Sand, f-c, Dark Yellow Orange									MW-8, Flushmount
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																																																								
0	5.75	Hydrovacuumed,																																																																																											
5.75	10	Silt, sandy (vf), some clay, Mod. Yellow Brown																																																																																											
10	16.3	Clay, silty, Dark Yellow Brown																																																																																											
16.3	18.5	Silt, sandy (vf), some clay, Mod. Yellow Brown																																																																																											
18.5	20	Clay, silty, Dark Yellow Brown																																																																																											
20	23.5	Clay, Pale Yellow Brown																																																																																											
23.5	25	Clay, Pale Yellow Brown																																																																																											
25	30	Clay, Dark Yellow Brown																																																																																											
30	32	Silt, sandy (f), Pale Yellow Brown																																																																																											
32	40	Clay, silty, Dark Yellowish Brown																																																																																											
40	43.5	Sand, f-m, silty, Light Gray to Gray Orange																																																																																											
43.5	45	Sand, f-c, Dark Yellow Orange																																																																																											
					MW-8, Flushmount																																																																																								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/18/2016 and this record is true to the best of my knowledge and belief.																																																																																													
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 5/31/2016																																																																																													
under the business name of GeoCore, Inc. by (signature) <i>Paul A. Hel</i>																																																																																													
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																																																													

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4