

1 LOCATION OF WATER WELL:

County: Saline

Fraction

NE ¼ SW ¼ NE ¼

Section Number

9

Township Number

T 14 S

Range Number

R 3 E

W

Distance and direction from nearest town or city street address of well if located within city?

1112 N. Halstead, Salina

2 WATER WELL OWNER:

RR#, St. Address, Box #

11720 Borman Drive

City, State, ZIP Code

St. Louis, MO 63146

Bunge North America, Inc.

Board of Agriculture, Division of Water Resources

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

N

W

E

S

NW

NE

SW

SE

X

4 DEPTH OF COMPLETED WELL 75 ft ELEVATION:

Depth(s) Groundwater Encountered 1. ft 2. ft 3. ft

WELL'S STATIC WATER LEVEL ft below land surface measured on mo/day/yr

Pump test data: Well water was NA ft after hours pumping gpm

Est. Yield NA gpm: Well water was ft after hours pumping gpm

Bore Hole Diameter 8 in. to 75 ft, and in. to ft

WELL WATER TO BE USED AS:

5 Public water supply

8 Air conditioning

11 Injection well

1 Domestic

3 Feedlot

6 Oil field water supply

9 Dewatering

12 Other (Specify below)

2 Irrigation

4 Industrial

7 Lawn and garden only

10 Monitoring

Was a chemical/bacteriological sample submitted to Department? Yes No ☒ ; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No ☒

5 TYPE OF BLANK CASING USED:

1 Steel

3 RMP (SR)

6 Asbestos-Cement

9 Other (specify below)

2 PVC

4 ABS

7 Fiberglass

CASING JOINTS: Glued Clamped

Blank casing diameter 2 in. to 64.5 ft, Dia 2 in. to 75 ft, Dia in. to ft

Casing height above land surface 40 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL

1 Steel

3 Stainless steel

5 Fiberglass

7 PVC

10 Asbestos-cement

2 Brass

4 Galvanized steel

6 Concrete tile

8 RMP (SR)

11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

10 Other (specify)

7 Torch cut

SCREEN-PERFORATED INTERVALS: From 64.5 ft to 74.5 ft, From ft to ft

From ft to ft, From ft to ft

GRAVEL PACK INTERVALS: From 57 ft to 75 ft, From ft to ft

From ft to ft, From ft to ft

6 GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout Intervals: From 0 ft to 1 ft, From 1 ft to 57 ft, From ft to ft

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well?

How many feet?

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 42 Silt, some clay, Dark Brown

42 72 Sand (m), Dark Gray

OBS6, Abovegrade

Project Name: BM - Cargill Salina

GeoCore # 1143, #

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/10/2008 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 2/26/2009

under the business name of GeoCore, Inc. by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.