			WATE	R WELL RECORD	Form WWC-				
		TER WELL:	Fraction	SW 1/4	I .	ction Number	Township		Range Number
County:		from pearent tow	n or city street a	SW 1/4 ddress of well if locat			T 14	· s	IR 3 EW
Distance at	na direction		959 TASKER		ed within City?				
d wazes	WELL OW		AL SWEENEY	2.4.12				 .	
	-		Casker Lane	7.			Board of	Agricultura	Division of Water Becourses
RR#, St. A City, State,			K.KS. 6740:					on Number:	Division of Water Resources
3 LOCATE	WELL'S I	OCATION WITH	A DEBTH OF C	OMBLETED WELL	60.6	4 ELEVA	7) 1241	JII Number.	
AN "X"	IN SECTIO								3
· [1								9-10-98
1	i		Pumr	ew iled water test test of	ter was	24 # a	ace measured of	on mo/day/yr	umping
-	- NW	NE	Fet Vield 7	5+ anm: Well wa	ter was	fr	ner	nours pu	umpingy gpm umping gpm
	1		Bore Hole Diame	eter 9 in to	61		nter	nours pu	umping gpm - to
W W	i			O BE USED AS:	5 Public wat		8 Air conditionir		Injection well
7	1	<u>i</u>	1 Domestic	3 Feedlot					Other (Specify below)
7	- SW	SE	2 Irrigation		7 Lawn and	garden only	10 Monitoring w	ell	
1 1			Was a chemical/t						, mo/day/yr sample was sub-
1 _			mitted	,			ter Well Disinfed		' ' ' ' ' ' ' ' ' ' ' ' ' ' '
5 TYPE O	F BLANK (CASING USED:		5 Wrought iron	8 Conci				d X Clamped
1 Ste	el	3 RMP (SR	R)	6 Asbestos-Cement	9 Other	(specify below	v)	Weld	led
2 PV		4 ABS		7 Fiberglass				Threa	aded
Blank casir	ng diameter	. 5 i	in. to <i>5</i> 44 •	6 ft., Dia	in. to)	ft., Dia		in. to ft.
Casing heigh	ght above la	and surface	18	.in., weight $oldsymbol{1}$	60	Ibs./	ft. Wall thickness	or gauge N	o SDR. 26
TYPE OF	SCREEN O	R PERFORATION	I MATERIAL:		_7_P\	<u>'C</u>	10 A:	sbestos-ceme	ent
1 Ste	el	3 Stainless	steel	5 Fiberglass	8 RM	MP (SR)	11 0	ther (specify)	
2 Bra		4 Galvanize		6 Concrete tile	9 AE	ss	12 N	one used (op	en hole)
		RATION OPENING			zed wrapped		8 Saw cut		11 None (open hole)
	ntinuous slo		I slot .035		wrapped		9 Drilled holes		
	vered shut		y punched	7 Tord	60 6		٠,	• •	
SCREEN-P	PERFORATI	ED INTERVALS:	From F.	<i></i>		IL., FIOI			o
_	DAVEL DA	OV INTERVALO.	From 45	π. το . ft. to .	60.6	π., Fror	n		o
G	HAVEL PA	CK INTERVALS:	From ∴					16. 6	O
6 GROUT	MATERIAL	.: 1 Neat ce		2 Cement grout			•		o #t.
Grout Inten	vals Fro	n 1		ft From	tt	to.	ft From		ft. to
		ource of possible of							bandoned water well
1 Septic tank 4 Lateral lines 7 Pit priv						10 Livestock pens 14 Abandoned water well 11 Fuel storage 15 Oil well/Gas well			
-	wer lines	5 Cess		8 Sewage lagoon		12 Fertilizer storage 16 Other (specify below)			
3 Wa	tertiaht sew	er lines 6 Seepa	•	9 Feedyard	,		ticide storage		
Direction fr		WEST	.	•		How mar	•	50	
FROM	TO		LITHOLOGIC I	LOG	FROM	TO		PLUGGING I	NTERVALS
0	3	FILL DIRT							
3	29	CLAY TAN		·					
29	61	SAND FINE	TO MED. I	'AN					
						ļ			
						 			
						-			
						+			
						-			
						 			
						+			
i						L			
أسين		^	'S CERTIFICATION						der my jurisdiction and was
completed of	on (mo/day								owledge and belief. Kansas
Water Well	Contractor'	s License No	J 00	This Water \	Vell Record wa				79/
		ne of PESTING					ure) Weef		uzio
INSTRUC of Health	TIONS: Use ty and Environm	pewriter or ball point poent, Bureau of Water, 1	en. <i>PLEASE PRESS FI.</i> Fopeka, Kansas 66620	RMLY and PRINT clearly. P 0-0001. Telephone: 913-296-	lease fill in blanks, 5545. Send one to	underline or circle WATER WELL OW	the correct answers. /NER and retain one	Send top three for your records	copies to Kansas Department