

LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: SALINE	SW 1/4 SW 1/4 NE 1/4	11	T 14 S	R 3 W

Distance and direction from nearest town or city street address of well if located within city?

515 N. 13th

WATER WELL OWNER:

R#, St. Address, Box #:

City, State, ZIP Code:

Robert Long**515 N. 13th****SALINA, KS 67401**

Board of Agriculture, Division of Water Resources


Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL:

55

ft. ELEVATION:

1227

Depth(s) Groundwater Encountered

1. 31

ft. 2.

ft. 3.

ft.

WELL'S STATIC WATER LEVEL

31

ft. below land surface measured on mo/day/yr

9-15-91

Pump test data: Well water was

34

ft. after

1

hours pumping

15 gpm

Est. Yield

20

gpm: Well water was

34

ft. after

1

hours pumping

15 gpm

Bore Hole Diameter

8 1/2

in. to

38

ft., and

5 1/2

in. to

55 ft.

WELL WATER TO BE USED AS:

5 Public water supply

8 Air conditioning

11 Injection well

1 Domestic

3 Feedlot

6 Oil field water supply

9 Dewatering

12 Other (Specify below)

2 Irrigation

4 Industrial

7 Lawn and garden only

10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes ☒ No ☐

TYPE OF BLANK CASING USED:

5 Wrought iron

8 Concrete tile

CASING JOINTS: Glued ☒ Clamped ☐

1 Steel

3 RMP (SR)

6 Asbestos-Cement

9 Other (specify below)

Welded

2 PVC

4 ABS

7 Fiberglass

Threaded

Blank casing diameter

5

in. to

45

ft. Dia

160 lb.

lbs./ft. Wall thickness or gauge No.

214

Casing height above land surface

22

in., weight

160 lb.

lbs./ft.

Wall thickness or gauge No.

214

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless steel

5 Fiberglass

8 RMP (SR)

10 Asbestos-cement

2 Brass

4 Galvanized steel

6 Concrete tile

9 ABS

11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

SCREEN-PERFORATED INTERVALS:

From

45

ft. to

55

ft. From

ft. to

ft.

From

45

ft. to

55

ft. From

ft. to

ft.

GRAVEL PACK INTERVALS:

From

21

ft. to

55

ft. From

ft. to

ft.

From

21

ft. to

55

ft. From

ft. to

ft.

GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout Intervals:

From

0

ft. to

21

ft. From

ft. to

21

ft. From

ft. to

ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well?

North & West

How many feet?

22 + 37

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	6'	Compacted dirt + silts			
6'	23'	fine SAND AND light brown clay mixed			
23'	38'	dark Brown clay			
38'	55'	medium to coarse SAND & gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was **1** constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **9-15-91** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. **523** This Water Well Record was completed on (mo/day/yr) **9-18-91**

under the business name of **M + S Well Service** by (signature) **Matthew Loukup**