

1 LOCATION OF WATER WELL: Fraction NW 1/4 SE 1/4 NW 1/4 Section Number 12 Township Number 14 S Range Number 3 E/W

County: Saline Distance and direction from nearest town or city street address of well if located within city? 5th & Lincoln Salina KS

2 WATER WELL OWNER: USPCS RR#, St. Address, Box #: 5665 Station City, State, ZIP Code: Boulder Colo 80301 Board of Agriculture, Division of Water Resources Application Number: mw-7

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section box with X in NW corner]

4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 32 ft. below land surface measured on mo/day/yr

WELL'S STATIC WATER LEVEL: 32 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 8 in. to 40 ft. after 40 hours pumping gpm

Est. Yield gpm: Well water was 8 in. to 40 ft. after 40 hours pumping gpm

Bore Hole Diameter: 8 in. to 40 ft. and 40 in. to 40 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded

Blank casing diameter: 2 in. to 30 ft. Dia. 30 in. to 30 ft. Dia. 30 in. to 30 ft. Dia.

Casing height above land surface: 30 in., weight 30 lbs./ft. Wall thickness or gauge No. 30

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft. From 30 ft. to 40 ft. From 30 ft. to 40 ft. From 30 ft. to 40 ft.

GRAVEL PACK INTERVALS: From 29 ft. to 40 ft. From 29 ft. to 40 ft. From 29 ft. to 40 ft. From 29 ft. to 40 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 29 ft. From 29 ft. to 40 ft. From 29 ft. to 40 ft. From 29 ft. to 40 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? WITHIN FACILITY How many feet?

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 37 Sandy Clay

37 TO Clayey sand

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-8-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) 3-5-92 under the business name of Layne Western, Wichita by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.