

1 LOCATION OF WATER WELL: County: Saline		Fraction SE ¼ SE ¼ SE ¼	Section Number 12	Township Number T 14 S	Range Number R 3 E/W
Distance and direction from nearest town or city street address of well if located within city? 418 East Ash, Salina, Kansas 67401					
2 WATER WELL OWNER: City of Salina RR#, St. Address, Box #: 300 West Ash City, State, ZIP Code: Salina, Ks. 67401					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;">N +-----+ NW NE +-----+ W X E +-----+ SW SE +-----+ S</div>		4 DEPTH OF COMPLETED WELL..... 44 ft. ELEVATION: Depth(s) Groundwater Encountered 1..... 34 ft. 2..... ft. 3..... ft. WELL'S STATIC WATER LEVEL 32.95 ft. below TOC measured on mo/day/yr 07-06-93 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter . 7 7/8 in. to 45 ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No....X.....; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 29 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 29 ft. to 44 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 27 ft. to 45 ft., From ft. to ft. From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 25 ft., From 25 ft. to 27 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? southwest How many feet? 315					
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0	26	BRN SLTY CLY			
26	31	VF TO F SND			MW 13
31	40	CLY/SND STRGS			Flush mount cover
40	44.5	F TO C SND/F GRVL			KDHE id # 00080921
44.5	45	GY SANDY CLY			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06-08-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 07-14-93 under the business name of GeoCore Services, Inc. by (signature) Dale A. Kelly					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					