

1) LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Saline		SW ¼ NW ¼ SW ¼	12	T 14 S	R 3 EW
Distance and direction from nearest town or city street address of well if located within city? 222 W. Elm, Salina					
2) WATER WELL OWNER: City of Salina					
RR#, St. Address, Box # : 300 West Ash		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Salina, KS 67401		Application Number:			
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4) DEPTH OF COMPLETED WELL: 40 ft. ELEVATION:				
<p>N W E S</p>	Depth(s) Groundwater Encountered 1. 30 ft. 2. ft. 3. ft.				
	WELL'S STATIC WATER LEVEL 28.74 ft. below TOC measured on mo/day/yr 06-30-93				
	Pump test data: Well water was ft. after hours pumping gpm				
	Est. Yield gpm: Well water was ft. after hours pumping gpm				
	Bore Hole Diameter 7 7/8 in. to 40 ft., and in. to ft.				
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No					
5) TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded Threaded
Blank casing diameter 2 in. to 25 ft., Dia.		7 Fiberglass			
Casing height above land surface 0 in., weight lbs./ft.		Wall thickness or gauge No. SCH. 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
1 Continuous slot		3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter		4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 25 ft. to 40 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 23 ft. to 40 ft., From ft. to ft.					
6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 21 ft., From 21 ft. to 23 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? WSW		How many feet? 100			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6"	Concrete			
6"	11	BRN SILTY CLY			
11	13.5	BRN CLYEY SILT			MW2
13.5	17	VF-F SND			#00079525
17	27	GY SILTY CLY-Contaminated			Flush Mount
27	39	GY CLY/SND SIRGS			
39	40	F-C SND/F GRVL			
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 06-10-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 5d7 This Water Well Record was completed on (mo/day/yr) 06-10-93 under the business name of GeoCore Services, Inc. by (signature) Dale Hall					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records					